



CONTACT

Market information
industryprojects.business@lynxeogroup.com

STANDARDS

Product EN 50575; IEC 60228

Installation NF F 55-625

APPLICATION

These cables are used for fixed power or lighting installations (1000 V) and fixed traction circuits (1800 V) in tunnels and underground stations.

FIRE RESISTANCE

- Flame retardant: According to RATP K20 specification
- Fire retardant: According to RATP K20 specification
- Low smoke: According to RATP K20 specification
- Without Halogene: According to RATP K20 specification
- Low Toxicity: According to RATP K20 specification
- Low Corrosivity: According to RATP K20 specification

Reaction to fire: B2ca-s1a, d0, a1

- **Conductor:** Flexible bare copper 5
- **Insulation :** Cross-linked polyethylene (XLPE)
- **Outer sheath:** Polyolefine without halogen, Colour : black

Core Identification

Black



Halogen free
IEC/EN 60754-1



Flame retardant
IEC/EN 60332-1-2



Smoke density
IEC 61034-2 & EN 61034-2



Gases corrosivity
IEC/EN 60754-2



Max. conductor temp. in service
90 °C



Operating temp.
-20 ... 60 °C

CHARACTERISTICS

Construction characteristics

Conductor material	Plain copper
Type of conductor	Flexible, Classe 5
Insulation	XLPE (Cross-linked Polyethylene)
Outer sheath	Halogen free polyolefin
Halogen free	IEC/EN 60754-1
With Green/Yellow core	No

Usage characteristics

Flame retardant	IEC/EN 60332-1-2
Smoke density	IEC 61034-2 & EN 61034-2
Gases corrosivity	IEC/EN 60754-2
Max. conductor temperature in service	90 °C
Operating temperature, range	-20 ... 60 °C

PRODUCT LIST

Reference	Country Ref.	Name	Conductor cross-section [mm²]	Maximum outer diameter [mm]	Approximate weight [kg/km]
☎ 13129515	-	NF F 55-625 (K25) 1000V 1x70 B2ca-s1a,d0,a1	70	22.2	351
☎ 10270837	-	NF F 55-625 (K25) 1800 V 1x16 B2ca-s1a, d0, a1	16	15.5	351
☎ 10270835	-	NF F 55-625 (K25) 1800 V 1x240 B2ca-s1a, d0, a1	240	34.0	2715

☎ = Make to order, 📦 = In stock,

COMPLEMENT

Bending Radius

- $r = 8 \times$ maximum outer diameter

SELLING AND DELIVERY INFORMATION

Marking

1000 V cables: 1000 - Nber of cores & cross-section - S - SH - NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 Manufacturing number DoP:1000291-FRME + metric marking

1800 V cables: 1800 - Nber of cores & cross-section - S - SH - NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 Manufacturing number DoP:1000291-FRME + metric marking