



CONTACT

Market information
industryprojects.business@lynxgroup.com

STANDARDS

Product EN 50575; EN 60228

Installation NF F 55-625

APPLICATION

These cables are used for fixed power or lighting installations in tunnels and underground stations.

FIRE PERFORMANCE

- Flame retardant: according to RATP K20 specification
- Fire retardant: according to RATP K20 specification
- Low smoke: according to RATP K20 specification
- Low toxicity: According to RATP K20 specification
- Low corrosivity: According to RATP K20 specification
- Without Halogen : According to RATP K20 specification

Reaction to fire: B2ca-s1a, d0, a1

DESIGN

- Conductor: Bare copper class 5
- Insulation: Cross-linked Polyethylene (XLPE)
- Assembling: An inner sheath acting as a filler
- Outer sheath: Polyolefin without halogen. Colour: black

Core identification

According to NF F 55625

2x: black - blue

3x: black - grey - brown

3G: black - blue - green/yellow

4x: black - blue - brown - black

4G: black - blue - brown - green/yellow

5G: black - blue - brown - black - green/yellow

≥ 7 conductors: black cores printed with numbers with or without green/yellow



无卤
IEC/EN 60754-1



阻燃 - 火焰
IEC/EN 60332-1-2



烟密度
IEC 61034-2 & EN 61034-2



气体腐蚀性
IEC/EN 60754-2



芯线最高静止温度
90 ° C



操作温度
-20 ... 60 ° C

CHARACTERISTICS

结构特性

导体材料	裸铜
绝缘	XLPE (Cross-linked Polyethylene)
外护套	无卤聚烯烃
无卤	IEC/EN 60754-1
有绿/黄芯线	无

尺寸特性

芯线数	2
导线截面	1.5 mm ²
Maximum outer diameter	11.5 mm
近似重量	161 kg/km

使用特性

阻燃 - 火焰	IEC/EN 60332-1-2
烟密度	IEC 61034-2 & EN 61034-2
气体腐蚀性	IEC/EN 60754-2
芯线最高静止温度	90 ° C
操作温度范围	-20 ... 60 ° C

PRODUCT LIST

Reference	Country Ref.	Name
10270798	-	NF F 55-625 (K25) 750V S2x1.5 B2ca-s1a, d0, a1

= Make to order, = In stock,

COMPLEMENT

Bending Radius

$r = 6 \times \text{maximum outer diameter}$

SELLING AND DELIVERY INFORMATION

Marking

750 V cables : 750 - Nber of cores & cross-section - S - SH - NF F 55-625 - LYNXEO 279 - WW - YY
- B2ca-s1a, d0, a1 - Manufacturing number DoP:1000148-FRME + metric marking



无卤
IEC/EN 60754-1



阻燃 - 火焰
IEC/EN 60332-1-2



烟密度
IEC 61034-2 & EN 61034-2



气体腐蚀性
IEC/EN 60754-2



芯线最高静止温度
90 ° C



操作温度
-20 ... 60 ° C

1000 V cables : 1000 - Nber of cores & cross-section - S - SH - NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 - Manufacturing number DoP:1000148-FRME + metric marking



无卤
IEC/EN 60754-1



阻燃 - 火焰
IEC/EN 60332-1-2



烟密度
IEC 61034-2 & EN 61034-2



气体腐蚀性
IEC/EN 60754-2



芯线最高静止温度
90 ° C



操作温度
-20 ... 60 ° C