



CONTACT

Market information
industryprojects.business@lynxgroup.com

ABS 1356 VNB, VNC, VND - Multi cores

Designed for general purpose aircraft wiring applications.

Screened and Jacketed Single and Multicores
 UV Laser Printable

STANDARDS

Product ABS 1356

Test prEN 3475

DESIGN CONSTRUCTION

CONDUCTOR

1 cores ABS 0949 AD

Nickel Copper Clad Aluminium

SCREEN

Nickel-plated copper spiral screen

JACKET

Polymide tape

UV PTFE tape

IDENTIFICATION

1 core (VNA) : Grey

Marking text : " XXX ** FR F++ "

Colour : Green for AWG 22, 18, 14 and 10 - Blue for AWG 24, 20, 16 and 12

JACKET IDENTIFICATION



Operating temp.
 -65 ... 180 °C



Oil resistance
 Very good resistance to aircraft fluids



RoHS compliant
 Yes

CHARACTERISTICS**Construction characteristics**

Number of conductors	1
----------------------	---

Electrical characteristics

Maximal operating frequency	0.0002 MHz
Operating voltage	600 V

Usage characteristics

Operating temperature, range	-65 ... 180 °C
Oil resistance	Very good resistance to aircraft fluids
Arc tracking resistant	Yes
RoHS compliant	Yes

PRODUCT LIST

Reference	Country Ref.	Screen strands nom. diam. [mm]	Max. DC resist at 20°C [Ohm/100m]	Nom. outer diam. [mm]	Max. outer diam. [mm]	Nominal weight [g/m]	Max. weight [g/m]
ABS 1356 VNA 18	10265759	0.08	33.2	2.03	2.11	9.73	10.4
ABS 1356 VNA 20	-	0.08	49.6	1.78	1.87	7.48	7.75
ABS 1356 VNA 22	-	0.08	90.2	1.51	1.6	5.58	5.86
ABS 1356 VNA 24	10064866	0.08	145	1.38	1.45	4.57	4.8
ABS 1356 VNA 12	-	0.1	10.9	3.09	3.2	22.56	24.3
ABS 1356 VNA 14	10064868	0.1	15.5	2.68	2.79	17.1	17.96
ABS 1356 VNA 16	10142974	0.1	23	2.38	2.48	13.64	14.51
ABS 1356 VNA 10	10093799	0.12	5.8	3.74	3.89	33.91	36.07