



Reference: 10112042
EAN 13: 3427580200366

CONTACT

Market information
industryprojects.business@lynxéo
ogroup.com

- Instrumentation cables 300/500 V
- XLPE insulation (Part 1)
- Unarmoured (Type 1)
- Overall Screen (OS)
- **Oil resistant**

STANDARDS

Ensayo IEC 60332-3-22 Cat.A

APPLICATIONS

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control where chemicals may be present.**

Design

Conductor:

Solid, stranded or flexible bare copper

Insulation:

Cross-linked polyethylene (XLPE)

Overall screen:

Binder tape

Tinned copper drain wire,

Aluminium/polyester tape

Outer sheath:

Polyvinyl chloride (PVC)

Colour: black

Other colour on request.

Core identification

Pair: black - white

Quad: black - white - red - blue (2 pair cables assembled as a quad)

White core printed with pair number

On request: according to PAS 5308 part 1

Marking

NEXANS 279 XLPE/OA.SCR/PVC 300/500V Nber of pairs & cross-section Cu IEC 60332-3-22(A) MM YYYY Manufacturing number + metric marking

Standards

PAS 5308 Part 1/type 1 (Design guide-lines)

BS EN 60228-2005

BS EN 50290-2-29

Resistencia a aceites

Sí

Resistencia a interferencias electromagnéticas

Sí

Temp. ambiente de utilización

-20 ... 60 °C

Max.conductor temp.in service


90 °C



Tensión nominal de servicio
Uo/U
300/500 V



No propagador del incendio
EN IEC 60332-3-22 (cat A)



Resistencia a aceites

Sí



Resistencia a interferencias electromagnéticas

Sí



Temp. ambiente de utilización

-20 ... 60 °C



Max.conductor temp.in service

90 °C

CHARACTERISTICS

Características de construcción

Material del conductor	Cobre desnudo
Type of conductor	Solid, Class 1
Aislamiento	XLPE
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Cubierta exterior	PVC
Protección	no

Características dimensionales

Sección del conductor	1 mm ²
Número de pares	30
Diámetro del conductor	1,14 mm
Diámetro sobre aislamiento	2,34 mm
Diámetro exterior mínimo	30,3 mm
Diámetro exterior máximo	33,4 mm
Peso aproximado	1320 kg/km

Características eléctricas

Tensión nominal de servicio U ₀ /U	300/500 V
---	-----------

Características de uso

No propagador del incendio	EN IEC 60332-3-22 (cat A)
Resistencia a aceites	Sí
Resistencia a interferencias electromagnéticas	Sí
Temperatura ambiente de utilización (rango)	-20 ... 60 °C
Temperatura máxima del conductor	90 °C
Standard	PAS

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

Tinned copper conductors available on request



Tensión nominal de servicio
U₀/U
300/500 V



No propagador del
incendio
EN IEC 60332-3-22 (cat
A)



Resistencia a aceites
Sí



Resistencia a interferencias
electromagnéticas
Sí



Temp. ambiente de
utilización
-20 ... 60 °C



Max. conductor temp. in
service
90 °C