



Reference: 10135101  
EAN 13: 3427580321429

#### CONTACT

Market information  
industryprojects.business@lyn  
xeogroup.com

- Instrumentation cables 170/300 V
- Overall Screen (OS)
- Oil resistant

#### STANDARDS

Test IEC 60331; IEC 60332 - 3 - 22 Cat.A

#### APPLICATIONS

These instrumentation and communication cable are used to transmit analogue or digital signals in measurement and process control .They are well adapted to underground use in industrial application where chemical and mechanical protections are needed (refinery areas, chemical plant...). They maintain circuit integrity when exposed to fire.

#### Design

##### Conductor:

Stranded bare copper class 2

##### Insulation:

Silicone rubber (Sil)

##### Overall screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

##### Bedding (inner sheath):

Low Smoke Zero Halogen (LSZH)

Colour: black

##### Armour:

Galvanized steel wires (SWA)

##### Outer sheath:

Polyvinyl chloride (PVC)

Colour: black

Other colour on request.

#### Core identification

Pair: white - black

Quad: white - black - red - blue (2 pair cables assembled as a quad)

White core printed with pair number



Uo/U  
170/300V



Mechanical  
resistance to  
impacts  
Good



Fire resistant  
IEC 60331



Fire retardant  
EN IEC  
60332 - 3 - 22 (cat



Oil resistance  
Yes



Electro magnetic  
interference  
resistance  
Yes



Operating temp.  
- 20 ... 60 ° C



Max. conductor  
temp.in service  
90 ° C

#### Marking

EXANS 279 SIL/OA.SCR/LSZH/SWA/PVC 170/300V Nber of pairs & cross - section  
Cu IEC 60331 IEC 60332 - 3 - 22(A) MM YYY YYY Manufacturing number + metric

marking

#### Standards

EN 50288 - 7 (Design guide - lines)

## CHARACTERISTICS

	2	( )
Overall screen	Tinned copper drain wire + aluminium/polyester tape Low smoke, zero halogen thermoplastic compound	
Armour type		
Protection	Yes	
Number of pairs	20	
	1 mm <sup>2</sup>	
	1.28 mm	
Diameter over insulation	2.44 mm	
Diameter over inner sheath	25.2 mm	
Diameter over armour	27.7 mm	
Minimum outer diameter	28.2 mm	
Maximum outer diameter	32.9 mm	
( )	1552 kg/km	
Uo/U (Um)	170/300V	
Mechanical resistance to impacts	Good	
Fire resistant	IEC 60331	
Fire retardant	EN IEC 60332 - 3 - 22 (cat A)	
Oil resistance	Yes	
Electro magnetic interference resistance	Yes	
操作度范	- 20 ... 60 ° C	
Max. conductor temperature in service	90 ° C	
Standard	EN	

## SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332 - 1 or IEC 60332 - 3 - 24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:

15 x outer diameter  
To be doubled during laying operations



Uo/U  
170/300V



Mechanical  
resistance to  
impacts  
Good



Fire resistant  
IEC 60331



Fire retardant  
EN IEC  
60332 - 3 - 22 (cat  
A)



Oil resistance  
Yes



Electro magnetic  
interference  
resistance  
Yes



Operating temp.  
- 20 ... 60 ° C



Max. conductor  
temp. in service  
90 ° C

Tinned copper conductors available on request



U<sub>o</sub>/U  
(U<sub>m</sub>)  
170/300V



Mechanical  
resistance to  
impacts  
Good



Fire resistant  
IEC 60331



Fire retardant  
EN IEC  
60332 - 3 - 22 (cat  
A)



Oil resistance  
Yes



Electro magnetic  
interference  
resistance  
Yes



Operating temp.  
- 20 ... 60 ° C



Max. conductor  
temp. in service  
90 ° C