



Reference: 10176329
Country Ref.: 01272423
EAN 13: 3427580464942

CONTACT

Market information
 industryprojects.business@lynxéo
 ogroup.com

Control cables CST 74C068 for nuclear power plants, 500V halogen-free. These cables, installed outside the containment area (K3), are unarmed and designed with copper braid shield.

STANDARDS

Product IEC 60228

Test IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

APPLICATIONS

These control cables allow connection to a variety of industrial equipment from control room. Many of them require anti-inductive screen (EMI).

CONSTRUCTION

Conductor:

- Stranded (class 2) or flexible (class 5) plain copper

Insulation:

- Zero halogen (SH), cross linked

Assembling:

- Polyester tape (optional)

Overall screen:

- Copper wire braid (CWB) R ≥ 80%

Outer sheath:

- Low smoke, zero halogen (LSZH)
- Colour: Grey

Core identification

Black cores printed with white numbers

Optional: with Y/G core

Marking

LYNXEO 279 Nber of cores & cross-section Cu EG CST 74 C 068 K3 SH 0.3/0.5 (0.6) kV YYYY Manufacturing number + metric marking



Halogen free
 IEC 60754-1; IEC 60754-2



Operating temp.
 -20 ... 60 °C



Smoke density
 EN/IEC 61034-2



Fire retardant
 NF C 32070 C1;
 IEC 60332-3-24
 (cat.B)



Electro magnetic
 interference
 resistance
 Yes



U.V resistance
 Yes



Life cycle 60years
 Yes



Max.conductor
 temp.in service
 90 °C

CHARACTERISTICS

Construction characteristics

Conductor material	Plain copper
Type of conductor	Stranded, class 2
Insulation	Halogen-free
Screen	Copper Braid
Outer sheath	LSZH
Halogen free	IEC 60754-1; IEC 60754-2

Dimensional characteristics

Conductor cross-section	1.5 mm ²
Number of cores	2
Conductor diameter	1.5 mm
Diameter over insulation	2.84 mm
Diameter over screen	6.2 mm
Minimum outer diameter	8.1 mm
Maximum outer diameter	9.4 mm
Approximate weight	135 kg/km

Electrical characteristics

Max. DC resistance of the conductor at 20°C	12.1 Ohm/km
Maximum DC resistance of the conductor at 90°C	15.400 Ohm/km
Reactance at 50 Hz	0.094 Ohm/km
Short Circuit Current 0,3 s Max	0.39 kA
Short Circuit Current 1 s Max	0.21 kA
Impedance at 50 Hz	12.1 Ohm
Voltage Drop	24.8 V/A.km
Calorific Power	1.2 MJ/m

Usage characteristics

Operating temperature, range	-20 ... 60 °C
Smoke density	EN/IEC 61034-2
Fire retardant	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Electro magnetic interference resistance	Yes
U.V resistance	Yes
Life cycle 60years	Yes
Max. conductor temperature in service	90 °C
Nuclear Classification	Class 1 E Non LOCA/K3

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations