



Reference: 10186691
EAN 13: 3427580519284

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

- Instrumentation cables 170/300 V
- With lead cover (LC)
- Overall Screen (OS)
- Aliphatic and aromatic hydrocarbons resistant

STANDARDS

Test IEC 60332 - 3 - 22 Cat.A

APPLICATIONS

These instrumentation and communication cables are used to transmit analogue or digital signals in measurement and process control. They are well adapted to underground use in industrial applications, in moist areas, where hydrocarbon and mechanical protection are needed. The lead cover brings an enhanced resistance to aromatics hydrocarbons.

Design

Conductor:

Stranded bare copper class 2

Insulation:

Cross - linked polyethylene (XLPE)

Overall screen:

Polyester tape

Tinned copper drain wire,

Aluminium backed polyester tape

Inner sheath:

Polyvinyl chloride (PVC)

Colour: black

Lead sheath:

Bedding (intermediate sheath):

Polyvinyl chloride (PVC)

Colour: black

Armour:

Galvanized steel wires (SWA)

Outer sheath:

Polyvinyl chloride (PVC)

Colour: black



Uo/U
170/300V



Mechanical
resistance to
impacts
Good



Fire retardant
EN IEC
60332-3
Cat. A



Chemical
resistance
Aliphatic
hydrocarbons
resistant



Electro magnetic
interference
standards
Yes



Operating temp.
- 20 ... 60 ° C



Max. conductor
temp. in service



Min. dynamic
operating bending
202.0 mm

Other colour on request.
Core identification

Pair: white - black
Quad (white) - black - red - blue (2 pair cables assembled as a quad)
White core marked with pair number

Marking

NEXANS 279 XLPE/OS-SCR/PVC/LC/PVC/SWA/PVC 170/300V Nber of pairs & cross section in IEC 60332-3 22 Cat.A Min. dynamic bending radius
All drawings, designs, specifications, plans and particulars of weights, size and dimensions shall not be binding on Lynxéo or be treated as constituting a representation on the part of Lynxéo.

Standards

CHARACTERISTICS

	2 ()
	XLPE(가)
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Lead Sheath	Yes
Intermediate sheath	PVC
Armour type	
Protection	Yes
Number of pairs	5
	0.75 mm ²
	1.1 mm
Diameter over insulation	1.58 mm
Diameter over inner sheath	10.1 mm
Diameter over lead sheath	12.1 mm
Diameter over intermediate sheath	14.1 mm
Diameter over armour	15.9 mm
Minimum outer diameter	18.3 mm
Maximum outer diameter	20.2 mm
()	933 kg/km
Uo/U (Um)	170/300V
Mechanical resistance to impacts	Good
Fire retardant	EN IEC 60332 - 3 - 22 (cat A)
Chemical resistance	Aliphatic and aromatic hydrocarbons resistant
Electro magnetic interference resistance	Yes
操作度范	- 20 ... 60 ° C
Max. conductor temperature in service	90 ° C
Minimum dynamic operating bending radius	202.0 mm
Standard	EN

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332 - 1 or IEC 60332 - 3 - 24(C) on request.



Uo/U
170/300V



Mechanical
resistance to
impacts
Good



Fire retardant
EN IEC
60332 - 3 - 22 (cat
A)



Chemical
resistance
Aliphatic and
aromatic
hydrocarbons
resistant



Electro magnetic
interference
resistance
Yes



Operating temp.
- 20 ... 60 ° C



Max. conductor
temp. in service
90 ° C



Min. dynamic
operating bending
rad.
202.0 mm

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

Tinned copper conductors available on request



Uo/U
(Um)
170/300V



Mechanical
resistance to
impacts
Good



Fire retardant
EN IEC
60332 - 3 - 22 (cat
A)



Chemical
resistance
Aliphatic and
aromatic
hydrocarbons
resistant



Electro magnetic
interference
resistance
Yes



Operating temp.
- 20 ... 60 ° C



Max. conductor
temp. in service
90 ° C



Min. dynamic
operating bending
rad.
202.0 mm