



Reference: 10192911
EAN 13: 3427580555039

CONTACT

Market information
industryprojects.business@lynxéo
ogroup.com

- Instrumentation cables 170/300 V
- Overall Screen (OS)
- **Oil resistant**

STANDARDS

Tests IEC 60332-3-22 Cat.A

APPLICATIONS

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control where chemicals may be present.**

Design

Conductor:

Stranded bare copper class 2

Insulation:

Cross-linked polyethylene (XLPE)

Overall screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

Outer sheath:

Polyvinyl chloride (PVC).

Colour: black.

Other colour on request.

Core identification

Pair: white - black

Quad: white - black - red - blue (2 pair cables assembled as a quad)

White core printed with pair number

Marking

NEXANS 279 XLPE/OA.SCR/PVC 170/300V Nber of pairs & cross-section Cu IEC 60332-3-22(A) MM YYYY Manufacturing number + metric marking

Standards

EN 50288-7 (Design guide-lines)



Nennspannung Uo/U
170/300V



Flammwidrig
EN IEC 60332-3-22 (cat A)



Ölbeständig
Ja



Elektromagnetisch geschirmt
Ja



Betriebstemp.
-20 ... 60 °C



Max. Betriebstemp. am Leiter
90 °C

CHARACTERISTICS**Konstruktionsmerkmale**

Leitermaterial	Kupfer, blank
Leitertyp	Stranded, class 2
Isolierung	VPE (vernetztes Polyethylen)
Gemeinsamer Schirm	Tinned copper drain wire + aluminium/polyester tape
Außenmantel	PVC
Schutz	Nein

Abmessungsmerkmale

Anzahl Paare	10
Leiterquerschnitt	0,5 mm ²
Durchmesser über Isolierung	1,38 mm
Außendurchmesser Mindestwert	13,0 mm
Leiterdurchmesser	0,9 mm
Maximaler Außendurchmesser	14,3 mm
Nettogewicht ca.	204 kg/km

Elektrische Eigenschaften

Nennspannung U _o /U	170/300V
--------------------------------	----------

Anwendungsmerkmale

Flammwidrig	EN IEC 60332-3-22 (cat A)
Ölbeständig	Ja
Elektromagnetisch geschirmt	Ja
Betriebstemperatur	-20 ... 60 °C
Max. Betriebstemperatur am Leiter	90 °C
Standard	EN

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

Tinned copper conductors available on request



Nennspannung U_o/U
170/300V



Flammwidrig
EN IEC 60332-3-22 (cat A)



Ölbeständig
Ja



Elektromagnetisch geschirmt
Ja



Betriebstemp.
-20 ... 60 °C



Max. Betriebstemp. am Leiter
90 °C