



**Reference:** 10192997  
**EAN 13:** 3427580555480

#### CONTACT

Market information  
industryprojects.business@lynxeogroup.com

- Instrumentation cables 170/300 V
- Overall Screen (OS)
- **Oil resistant**

#### STANDARDS

**Tests** IEC 60332-3-22 Cat.A

#### APPLICATIONS

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control where chemicals may be present.**

#### Design

##### Conductor:

Stranded bare copper class 2

##### Insulation:

Cross-linked polyethylene (XLPE)

##### Overall screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

##### Outer sheath:

Polyvinyl chloride (PVC).

Colour: black.

Other colour on request.

#### Core identification

Pair: white - black

Quad: white - black - red - blue (2 pair cables assembled as a quad)

White core printed with pair number

#### Marking

NEXANS 279 XLPE/OA.SCR/PVC 170/300V Nber of pairs & cross-section Cu IEC 60332-3-22(A) MM YYYY Manufacturing number + metric marking

#### Standards

EN 50288-7 (Design guide-lines)



Nennspannung Uo/U  
170/300V



Flammwidrig  
EN IEC 60332-3-22 (cat A)



Ölbeständig  
Ja



Elektromagnetisch geschirmt  
Ja



Betriebstemp.  
-20 ... 60 °C



Max. Betriebstemp. am Leiter  
90 °C

**CHARACTERISTICS****Konstruktionsmerkmale**

Leitermaterial	Kupfer, blank
Leitertyp	Stranded, class 2
Isolierung	VPE (vernetztes Polyethylen)
Gemeinsamer Schirm	Tinned copper drain wire + aluminium/polyester tape
Außenmantel	PVC
Schutz	Nein

**Abmessungsmerkmale**

Anzahl Paare	20
Leiterquerschnitt	2,5 mm <sup>2</sup>
Durchmesser über Isolierung	2,57 mm
Außendurchmesser Mindestwert	27,4 mm
Leiterdurchmesser	1,91 mm
Maximaler Außendurchmesser	30,2 mm
Nettogewicht ca.	1210 kg/km

**Elektrische Eigenschaften**

Nennspannung U <sub>o</sub> /U	170/300V
--------------------------------	----------

**Anwendungsmerkmale**

Flammwidrig	EN IEC 60332-3-22 (cat A)
Ölbeständig	Ja
Elektromagnetisch geschirmt	Ja
Betriebstemperatur	-20 ... 60 °C
Max. Betriebstemperatur am Leiter	90 °C
Standard	EN

**SELLING AND DELIVERY INFORMATION**

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:

10 x outer diameter  
To be doubled during laying operations

Tinned copper conductors available on request



Nennspannung U<sub>o</sub>/U  
170/300V



Flammwidrig  
EN IEC 60332-3-22 (cat A)



Ölbeständig  
Ja



Elektromagnetisch geschirmt  
Ja



Betriebstemp.  
-20 ... 60 °C



Max. Betriebstemp. am Leiter  
90 °C