



**Reference:** 10194810  
**EAN 13:** 3427580564970

#### CONTACT

Market information  
industryprojects.business@lynxeogroup.com

Control cables CST 74C068 for nuclear power plants, 500V halogen-free. These cables, installed outside the containment area (K3), are unarmed and designed with copper braid shield.

#### STANDARDS

**Product** IEC 60228

**Test** IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

#### APPLICATIONS

These control cables allow connection to a variety of industrial equipment from control room. Many of them require anti-inductive screen (EMI).

#### CONSTRUCTION

##### Conductor:

- Stranded (class 2) or flexible (class 5) plain copper

##### Insulation:

- Zero halogen (SH), cross linked

##### Assembling:

- Polyester tape (optional)

##### Overall screen:

- Copper wire braid (CWB) R ≥ 80%

##### Outer sheath:

- Low smoke, zero halogen (LSZH)
- Colour: Grey

#### Core identification

Black cores printed with white numbers

Optional: with Y/G core

#### Marking

LYNXEO 279 Nber of cores & cross-section Cu EG CST 74 C 068 K3 SH 0.3/0.5 (0.6) kV YYYY Manufacturing number + metric marking



Halogen free  
IEC 60754-1; IEC 60754-2



Operating temp.  
-20 ... 60 °C



Smoke density  
EN/IEC 61034-2



Fire retardant  
NF C 32070 C1;  
IEC 60332-3-24  
(cat.B)



Electro magnetic  
interference  
resistance  
Yes



U.V resistance  
Yes



Life cycle 60years  
Yes



Max.conductor  
temp.in service  
90 °C

## CHARACTERISTICS

### Construction characteristics

Conductor material	Plain copper
Type of conductor	Flexible, Classe 5
Insulation	Halogen-free
Screen	Copper Braid
Outer sheath	LSZH
Halogen free	IEC 60754-1; IEC 60754-2

### Dimensional characteristics

Conductor cross-section	1 mm <sup>2</sup>
Number of cores	4
Conductor diameter	1.3 mm
Diameter over insulation	2.58 mm
Diameter over screen	6.8 mm
Minimum outer diameter	8.8 mm
Maximum outer diameter	10.3 mm
Approximate weight	160 kg/km

### Electrical characteristics

Max. DC resistance of the conductor at 20°C	19.5 Ohm/km
Maximum DC resistance of the conductor at 90°C	24.800 Ohm/km
Reactance at 50 Hz	0.1 Ohm/km
Short Circuit Current 0,3 s Max	0.26 kA
Short Circuit Current 1 s Max	0.14 kA
Impedance at 50 Hz	19.5 Ohm
Voltage Drop	39.8 V/A.km
Calorific Power	1.4 MJ/m

### Usage characteristics

Operating temperature, range	-20 ... 60 °C
Smoke density	EN/IEC 61034-2
Fire retardant	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Electro magnetic interference resistance	Yes
U.V resistance	Yes
Life cycle 60years	Yes
Max. conductor temperature in service	90 °C
Nuclear Classification	Class 1 E Non LOCA/K3

## SELLING AND DELIVERY INFORMATION

### Minimum bending radius:

10 x outer diameter  
To be doubled during laying operations