



Reference: 10284054
EAN 13: 3427580835452

FIRE PERFORMANCE CLASS



B2ca-s1a,d0,a1

CONTACT

Market information
industryprojects.business@lynxéo
ogroup.com

STANDARDS

Product EN 50575; EN 60228

Installation NF F 55-625

APPLICATION

These cables are used for fixed power or lighting installations (1000 V) and fixed traction circuits (1800 V) in tunnels and underground stations.

FIRE PERFORMANCE

- Flame retardant: According to RATP K20 specification
- Fire retardant: According to RATP K20 specification
- Low smoke: According to RATP K20 specification
- Without Halogen: According to RATP K20 specification
- Low Toxicity : According to RATP K20 specification
- Low corrosivity: According to RATP K20 specification

Reaction to fire: B2ca-s1a, d0, a1

DESIGN

- **Conductor:** Bare copper class 1 or 2
- **Insulation:** Cross-linked polyethylene (XLPE)
- **Outer sheath:** Polyolefine without halogen
Colour : black or yellow/green (Y/G)

Core identification

According to NF F 55625
1x: black



Halogen free
IEC/EN 60754-1



Flame retardant
IEC/EN 60332-1-2



Smoke density
IEC 61034-2 & EN 61034-2



Gases corrosivity
IEC/EN 60754-2



Max. conductor temp. in service
90 °C



Operating temp.
-20 ... 60 °C

CHARACTERISTICS

Construction characteristics

Type of conductor	Stranded, class 2
Conductor material	Plain copper
Insulation	XLPE (Cross-linked Polyethylene)
Outer sheath	Halogen free polyolefin
Halogen free	IEC/EN 60754-1
Sheath colour	Black

Dimensional characteristics

Conductor cross-section	120 mm ²
Maximum outer diameter	26.0 mm
Approximate weight	1424 kg/km

Usage characteristics

Flame retardant	IEC/EN 60332-1-2
Smoke density	IEC 61034-2 & EN 61034-2
Gases corrosivity	IEC/EN 60754-2
Max. conductor temperature in service	90 °C
Operating temperature, range	-20 ... 60 °C

COMPLEMENT

Bending Radius

$r = 6 \times \text{maximum outer diameter}$

SELLING AND DELIVERY INFORMATION

Marking

1000 V cables: 1000 - Nber of cores & cross-section - SH -NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 - Manufacturing n° + metric marking

1800 V cables: 1800 - Nber of cores & cross-section - SH -NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 - Manufacturing n° + metric marking