

**Reference:** 13110148  
**EAN 13:** 3427580849589

## FIRE PERFORMANCE CLASS



Cca-s1b,d1,a1

## CONTACT

Market information  
[industryprojects.business@lynxeogroup.com](mailto:industryprojects.business@lynxeogroup.com)

- 12/20(24)kV
- Non-armoured
- Low smoke, zero halogen (LSZH)

## STANDARDS

**Test** IEC 60332-3-24; NF C32-070/C1

## DESIGN

- **Conductor:** Stranded plain copper (class 2)
- **Semi conductor**
- **Insulation:** Ethylene propylene rubber (EPR)
- **Insulation screen:** Semi conductor and copper tapes
- **Outer sheath:** Low smoke, zero halogen (LSZH)

## Marking

LYNXEO 279 - EPR/LSZH - 12/20 kV - Nb of cores & cross-section - Cu - MM YYYY - Cca-s1b, d1, a1 - Manufacturing N° + metric marking

## Core identification

1x: naturel



Halogen free  
 IEC 60754-1



Operating temp.  
 -20 ... 60 °C



Gases corrosivity  
 IEC 60754-2



Smoke density  
 IEC 61034-2



Max. conductor temp. in service  
 90 °C



Fire retardant  
 NF C 32-070 C1, IEC 60332-3-24 (cat.C)

**CHARACTERISTICS****Construction characteristics**

Conductor material	Plain copper
Type of conductor	Stranded, class 2
Insulation	EPR
Outer sheath	LSZH compound
Halogen free	IEC 60754-1

**Dimensional characteristics**

Number of cores	1
Conductor cross-section	25 mm <sup>2</sup>
Approximate weight	1200 kg/km
Maximum outer diameter	33.0 mm
Minimum outer diameter	29.5 mm

**Usage characteristics**

Operating temperature, range	-20 ... 60 °C
Gases corrosivity	IEC 60754-2
Smoke density	IEC 61034-2
Max. conductor temperature in service	90 °C
Fire retardant	NF C 32-070 C1, IEC 60332-3-24 (cat.C)