



Reference: 79462630

### CONTACT

Markets and Products Information  
rollingstock.business@lynxeogroup.com

## SHEATHED SINGLE CORE POWER CABLES

FLAMEX® EN 50264 - 3 - 1 3600V MM power cables are used for fixed and protected installations. This product range is recommended for narrow spaces where an optimal bending radius is required. FLAMEX® cables are designed to withstand tough working conditions (oil, ozone, temperature variation, etc.). 120 °C conductor temperature is allowed for a 20,000 hours cumulative working time.

### STANDARDS

Product EN 50264 - 3 - 1; EN 45545 - HL3; IEC 60228

### DESIGN

1. Conductor  
Flexible stranded tinned copper class 5 acc. to IEC 60228  
Conductor screen
2. Insulation  
Cross - linked compound type EI 109 acc. to EN 50264 - 1  
Colour: grey
3. Sheath  
Cross - linked compound type EM 104 acc. to EN 50264 - 1  
Oil, diesel, ozone and UV resistant  
Colour: black

Example of marking: FLAMEX EN 50264 - 3 - 1 3600V (mm<sup>2</sup>) MM  
NSHXAFOE 3.6/6kV | LYNXEO | WW - YYYY

### GUIDE TO USE

- Cabling rules are given in EN 50343 and EN 50355
- Permissible current carrying capacities: values and calculation method are given in EN 50343
- Bending radius:
  - Static use: 4 x outer cable diameter (5 x D if D > 10mm)
  - For installation and occasional movements: 10 x outer cable diameter



Conductor flexibility  
5



Halogen free  
EN 60754 - 1 & EN 60684 - 2



Uo/U  
(Um)  
3.6 / 6 (7.2) kV



EN 60332 - 1 - 2



Fire retardant  
EN IEC 60332 - 3 - 24 (cat C); EN IEC 60332 - 3 - 25 (EN50305)



EN/IEC 61034 - 2



가  
EN 50305 - 9.2



Operating temp.  
- 40 ... 90 °C

## CHARACTERISTICS

Conductor flexibility	Tin plated copper	
	5	
Halogen free	Cross - linked compound	
	Cross - linked compound	
	EN 60754 - 1 & EN 60684 - 2	
Minimum outer diameter Maximum outer diameter (      )	6 mm <sup>2</sup>	
	10.3 mm	
	10.7 mm	
	160 kg/km	
U <sub>o</sub> /U (U <sub>m</sub> )	- mm	
	3.6 / 6 (7.2) kV	
Fire retardant	EN 60332 - 1 - 2	
	EN IEC 60332 - 3 - 24 (cat C); EN IEC 60332 - 3 - 25 (EN50305)	
가 操作度范	EN/IEC 61034 - 2	
	EN 50305 - 9.2	
Max. conductor temperature in service	- 40 ... 90 ° C	
Overload maximum core temperature	90 ° C	
Chemical resistance	- ° C	
Ozone resistance	Excellent	
U.V resistance	Yes	
Short - circuit max. conductor temperature	Yes	
	200 ° C	