



Reference: 79463101

CONTACT

Markets and Products Information
rollingstock.business@lynxeogroup.com

SINGLE CORE POWER CABLES

FLAMEX® EN 50264-3-1 600V M power cables are used for fixed and protected installations. This product range is recommended for narrow spaces where an optimal bending radius is required. FLAMEX® cables are designed to withstand tough working conditions (oil, ozone, temperature variation, etc.). 120° C conductor temperature is allowed for a 20,000 hours cumulative working time.

STANDARDS

Product EN 50264-3-1; EN 45545 - HL3; IEC 60228

DESIGN

1. Conductor

Flexible stranded tinned copper class 5 acc. to IEC 60228
Optional halogen-free separator tape

2. Insulation

Cross-linked compound type EI 109 acc. to EN 50264-3-1
Oil, diesel, ozone and UV resistant
Colour: black (or optionally green/yellow for earthing wires)

Example of marking: FLAMEX EN 50264-3-1 600V mm² M (N)HXAF 0,6/1kV I
NEXANS I WW-YYYY



导线柔软度
柔软等级5



无卤
EN 60754-1 & EN
60684-2



额定电压U₀/U
0.6/ 1 (1.2) kV



阻燃 - 火焰
IEC 60332-1-2



阻燃
EN IEC 60332-3-24
(cat. C); EN IEC
60332-3-25
(EN50305)



烟密度
EN/IEC 61034-2



气体毒性
EN 50305-9.2



操作温度
-40 ... 90 ° C

CHARACTERISTICS

结构特性

导体材料	Tin plated copper
导线柔软度	柔软等级5
绝缘	Cross-linked compound
无卤	EN 60754-1 & EN 60684-2

尺寸特性

导线截面	50 mm ²
外径最小值	11.3 mm
Maximum outer diameter	11.9 mm
近似重量	477 kg/km
导线直径	- mm

电气特性

额定电压U ₀ /U	0.6/ 1 (1.2) kV
-----------------------	-----------------

使用特性

阻燃 - 火焰	IEC 60332-1-2
阻燃	EN IEC 60332-3-24 (cat C); EN IEC 60332-3-25 (EN50305)
烟密度	EN/IEC 61034-2
气体毒性	EN 50305-9.2
操作温度范围	-40 ... 90 ° C
芯线最高静止温度	90 ° C
Overload maximum core temperature	- ° C
耐化学物质	好
Ozone resistance	是
抗UV	是
短路最高线芯温度	200 ° C