



Reference: 79463431

CONTACTMarkets and Products Information
rollingstock.business@lynxeogroup.com**SHIELDED SINGLE CORE POWER CABLES**

FLAMEX® EN 50264-3-1 3600V MMS shielded power cables are used for protected installations where enhanced electrical screening (EMC) is required. This product range is recommended for installations and connections in narrow spaces where an optimal bending radius is required. FLAMEX® cables are designed to withstand tough working conditions (oil, ozone, temperature variation, etc.). 120°C conductor temperature is allowed for a 20,000 hours cumulative working time.

STANDARDS

Product EN 50264-3-1; EN 45545 - HL3; IEC 60228

DESIGN**1. Conductor**

Flexible stranded tinned copper, class 5 acc. to IEC 60228
Optional halogen-free separator tape

2. Insulation

Cross-linked compound type EI 109 acc. to EN 50264-1
Colour: black or grey

3. Screen

Halogen-free foil, tinned copper wire braid, halogen-free separator

4. Outer sheath

Cross-linked compound type EM 104 acc. to EN 50264-1
Oil, diesel, ozone and UV resistant
Colour: black

Example of marking: FLAMEX EN 50264-3-1 3600V (mm²) MM (N)SHXAFCOE
3.6/6 kV | LYNXEO | WW-YYYY

GUIDE TO USE

- Cabling rules are given in EN 50343 and EN 50355
- Permissible current carrying capacities: values and calculation method are given in EN 50343
- Bending radius:
 - Static use: 5 x outer cable diameter (6 x D if D > 10mm)
 - For installation and occasional movements: 10 x outer cable diameter

Conductor flexibility
Flexible class 5Halogen free
EN 60754-1 & EN
60684-2Rated Voltage Uo/U
(Um)
3.6 / 6 (7.2) kVFlame retardant
IEC 60332-1-2Fire retardant
EN IEC 60332-3-24
(cat C); EN IEC
60332-3-25
(EN50305)Smoke density
EN/IEC 61034-2Gases toxicity
EN 50305-9.2Electro magnetic
interference
resistance
Yes

CHARACTERISTICS

Construction characteristics

Conductor material	Tin plated copper
Conductor flexibility	Flexible class 5
Insulation	Cross-linked compound
Screen	Tinned copper braid
Outer sheath	Cross-linked compound
Halogen free	EN 60754-1 & EN 60684-2

Dimensional characteristics

Conductor cross-section	120 mm ²
Minimum outer diameter	24.4 mm
Maximum outer diameter	25.0 mm
Approximate weight	1560 kg/km
Braid section	16 mm ²
Number of cores	1

Electrical characteristics

Rated Voltage U _o /U (U _m)	3.6 / 6 (7.2) kV
---	------------------

Usage characteristics

Flame retardant	IEC 60332-1-2
Fire retardant	EN IEC 60332-3-24 (cat C); EN IEC 60332-3-25 (EN50305)
Smoke density	EN/IEC 61034-2
Gases toxicity	EN 50305-9.2
Electro magnetic interference resistance	Yes
Operating temperature, range	-40 ... 90 °C
Max. conductor temperature in service	90 °C
Overload maximum core temperature	120 °C
Chemical resistance	Excellent
Ozone resistance	Yes
U.V resistance	Yes
Fire load	1.9 kWh/m
Short-circuit max. conductor temperature	200 °C