



Reference: 79466713

### CONTACT

Markets and Products Information  
rollingstock.business@lynxeogroup.com

## SHIELDED MULTICORES POWER CABLES

FLAMEX® EN 50264 - 3 - 2 600V MMS multicores shielded power and control cables are used for protected installations where enhanced electrical screening (EMC) is required. This product range is recommended for installations and connections in narrow spaces where an optimal bending radius is required. FLAMEX® cables are designed to withstand tough working conditions (oil, ozone, temperature variation, etc.). 120 °C conductor temperature is allowed for a 20,000 hours cumulative working time.

### STANDARDS

Product EN 50264 - 3 - 2; EN 45545 - HL3; IEC 60228

### DESIGN

#### 1. Conductor

Flexible stranded tinned copper class 5 acc. to IEC 60228  
Optional halogen - free separator tape

#### 2. Insulation

Cross - linked compound type EI 109 acc. to EN 50264 - 1  
Colour: black (or green/yellow if cable type is G)  
Assembly (option): halogen free foil could be served

#### 3. Screen

Copper wire braid acc. to EN 50264 - 3 - 2, halogen - free separator

#### 4. Outer sheath

Cross - linked compound type EM 104 acc. to EN 50264 - 1  
Oil, diesel, ozone and UV resistant  
Colour: black

Example of marking: FLAMEX EN 50264 - 3 - 2 600V n X (or G) ... (mm<sup>2</sup>) MM  
S (N)HXCSLOE I LYNXEO I WW - YYYY

### GUIDE TO USE

- Cabling rules are given in EN 50343 and EN 50355
- Permissible current carrying capacities: values and calculation method are given in EN 50343
- Bending radius:
- Static use: 4 x outer cable diameter
- For installation and occasional movements: 8 x outer cable diameter



Conductor flexibility  
5



Halogen free  
EN 60754 - 1 & EN 60684 - 2



Uo/U  
(Um)  
0.6/ 1 (1.2) kV



EN 60332 - 1 - 2



Fire retardant  
EN IEC 60332 - 3 - 24 (cat C); EN IEC 60332 - 3 - 25 (EN50305)



EN/IEC 61034 - 2



가  
EN 50305 - 9.2



Electro magnetic interference resistance  
-

## CHARACTERISTICS

Conductor flexibility	Tin plated copper	
	5	
	Cross - linked compound	
	Cross - linked compound	
Halogen free	EN 60754 - 1 & EN 60684 - 2	
With Green/Yellow core		
	3	
	10 mm <sup>2</sup>	
Minimum outer diameter	17.0 mm	
Maximum outer diameter	18.0 mm	
( )	529 kg/km	
	- mm	
Uo/U (Um)	0.6/ 1 (1.2) kV	
Fire retardant	EN 60332 - 1 - 2	
	EN IEC 60332 - 3 - 24 (cat C); EN IEC 60332 - 3 - 25 (EN50305)	
가	EN/IEC 61034 - 2	
	EN 50305 - 9.2	
Electro magnetic interference resistance	-	
操作度范	- 40 ... 90 ° C	
Max. conductor temperature in service	90 ° C	
Overload maximum core temperature	- ° C	
Chemical resistance	Excellent	
Ozone resistance	Yes	
U.V resistance	Yes	
Short - circuit max. conductor temperature	200 ° C	