



**Reference:** Etude 132909  
**Country Ref.:** Etude 132909

## CONTACT

Market information  
industryprojects.business@lynx  
ogroup.com

### International Designation:

34 channels 38 AWG coax cable

Ultrasound cable assemblies

## STANDARDS

**Product** 448-010-3-10; Nexans specification

### Characteristics

Very flexible cable with an extremely good mechanical behaviour.  
Withstands miscellaneous sterilisation processes.

### CONSTRUCTION

#### 1- CORE (A)

AWG 38 silver plated copper wire.  
FEP insulation.  
Diameter : 0.30 +/- 0.02 mm

AWG 48 silver plated copper helical screen  
Nominal diameter : 0.36 mm

FEP jacket  
Diameter : 0.53 +/- 0.03 mm

#### 2- CORE (B)

8 Cores A twisted.  
Nominal diameter : 1.63 mm

#### 3- CORE (C)

2 Cores (A) twisted.  
Nominal diameter : 1.07 mm

1 Kevlar strength member +  
4 cores (B) + 1 core (C) twisted.  
Nominal diameter : 3.70 mm

#### 4- PTFE Tape

Nominal diameter : 3.84 mm

#### 5- SHIELD

AWG 40 tin plated copper braid.  
85% coverage.  
Nominal diameter : 4.20 mm

#### 6- JACKET

Medical PVC  
Diameter : 5.97 +/- 0.10 mm

### Main Characteristics

Minimum bending radius : 5 x Overall diameter.



Cable flexibility  
**Very flexible**



Maximum operating temperature  
**85 °C**



Minimum operating temperature  
**-30 °C**



RoHS compliant  
**Yes**

**CHARACTERISTICS****Construction characteristics**

Construction type	Shielded and sheathed
Conductor shape	Single wired
Conductor material	Silver coated copper
Insulation	FEP

**Dimensional characteristics**

Approximate weight	53 g/m
Outer Diameter	5.97 mm

**Electrical characteristics**

Operating voltage	24 V
-------------------	------

**Mechanical characteristics**

Cable flexibility	Very flexible
-------------------	---------------

**Usage characteristics**

Maximum operating temperature	85 °C
Minimum operating temperature	-30 °C
RoHS compliant	Yes