



Country Ref.: Etude 132807

### CONTACT

Market information  
industryprojects.business@lynxgroup.com

### International Designation:

2 channels 32 AWG coax  
+ 1 channel 32 AWG triax  
+ 4 x 26 AWG wires

### Ultrasound cable assemblies

Very flexible cable with an extremely good mechanical behaviour.  
Withstands miscellaneous sterilisation processes.

## STANDARDS

Product 448-010-3-10; Nexans specification

### 1- CORE (A)

AWG 32 stranded Silver plated copper alloy conductor.  
FEP insulation.  
Diameter : 0.65 +/- 0.02 mm.  
AWG 44 Silver plated copper spiral shield.  
Nominal diameter : 0.75 mm.  
FEP jacket  
Diameter : 0.91 +/- 0.03 mm

### 2- CORE (B)

32 AWG stranded Silver plated copper alloy conductor.  
FEP insulation.  
Diameter : 0.65 +/- 0.02 mm.  
AWG 44 Silver plated copper spiral shield.  
Nominal diameter : 0.75 mm  
FEP jacket.  
Nominal diameter : 0.91 +/- 0.03 mm.  
AWG 44 Silver plated copper spiral shield.  
Nominal diameter : 1.01 mm.  
FEP jacket.  
Diameter : 1.20 +/- 0.10 mm.

### 3- CORE (C)

AWG 26 stranded Silver plated copper conductor.  
FEP insulation.  
Diameter : 0.91 +/- 0.05 mm

### Assembly

1 Core (B) + 1 Kevlar member  
Around 2 Cores (A) + 1 filler + 4 Cores (C) twisted.  
Nominal diameter : 3.00 mm

### 4- PTFE Tape

Nominal diameter : 3.05 mm

### 5- SHIELD

AWG 40 Silver plated copper braid.  
85% coverage.  
Nominal diameter : 3.50 mm

### 6- JACKET

Medical PVC  
Diameter : 6.80 +/- 0.15 mm



Cable flexibility  
Very flexible



Maximum operating temperature  
85 °C



Minimum operating temperature  
-30 °C



RoHS compliant  
Yes

### Main Characteristics

Minimum bending radius : 5 x Overall diameter.

**CHARACTERISTICS****Construction characteristics**

Construction type	Shielded and sheathed
Conductor shape	Single wired
Conductor material	Silver coated copper
Insulation	FEP

**Dimensional characteristics**

Approximate weight	62 g/m
Outer Diameter	6.8 mm

**Electrical characteristics**

Operating voltage	24 V
-------------------	------

**Mechanical characteristics**

Cable flexibility	Very flexible
-------------------	---------------

**Usage characteristics**

Maximum operating temperature	85 °C
Minimum operating temperature	-30 °C
RoHS compliant	Yes