



Country Ref.: Etude 123836

CONTACT

Market information
industryprojects.business@lynxgroup.com

International Designation:

32 AWG coax cable

Ultrasound cable assemblies

Very flexible cable with an extremely good mechanical behaviour.
Withstands miscellaneous sterilisation processes.

STANDARDS

Product Nexans specification

1- Conductor

AWG 32 stranded silver plated copper alloy.

2- Insulation

FEP

Diameter : 0.65 +/- 0.03 mm

3- Shield

AWG 44 silver plated copper spiral shield

Nominal diameter : 0.75 mm

4- Jacket

FEP

Diameter : 0.91 +/- 0.03 mm

Main Characteristics

Minimum bending radius : 5 x Overall diameter.



Cable flexibility
Very flexible



Maximum operating temperature
200 °C



Minimum operating temperature
-50 °C



RoHS compliant
Yes

CHARACTERISTICS**Construction characteristics**

Construction type	Shielded and sheathed
Conductor shape	Multi stranded
Conductor material	Silver coated copper
Insulation	FEP

Dimensional characteristics

Approximate weight	2.11 g/m
Outer Diameter	0.91 mm

Electrical characteristics

Operating voltage	24 V
-------------------	------

Mechanical characteristics

Cable flexibility	Very flexible
-------------------	---------------

Usage characteristics

Maximum operating temperature	200 °C
Minimum operating temperature	-50 °C
RoHS compliant	Yes