



Country Ref.: Etude 132662

### CONTACT

Market information  
industryprojects.business@lynxeogroup.com

#### International Designation:

32 AWG coax cable

#### Ultrasound cable assemblies

Very flexible cable with an extremely good mechanical behaviour.  
Withstands miscellaneous sterilisation processes.

### STANDARDS

Product 448-010-3-10; Nexans specification

#### 1- Conductor

AWG 32 stranded silver plated copper alloy.

#### 2- Insulation

FEP

Diameter : 0.65 +/- 0.03 mm

#### 3- Shield

AWG 44 silver plated copper spiral shield

Nominal diameter : 0.75 mm

#### 4- FEP Jacket

Diameter : 0.91 +/- 0.03 mm

#### 5- Polyamide Jacket

Diameter : 1.30 +/- 0.05 mm

Good adhesion between FEP and Polyamide.

#### Main Characteristics

Minimum bending radius : 5 x Overall diameter.



Cable flexibility  
Very flexible



Maximum operating temperature  
105 °C



Minimum operating temperature  
-50 °C



RoHS compliant  
Yes

**CHARACTERISTICS****Construction characteristics**

Construction type	Shielded and sheathed
Conductor shape	Multi stranded
Conductor material	Silver coated copper
Insulation	FEP

**Dimensional characteristics**

Approximate weight	3.7 g/m
Outer Diameter	1.3 mm

**Electrical characteristics**

Operating voltage	250 V
-------------------	-------

**Mechanical characteristics**

Cable flexibility	Very flexible
-------------------	---------------

**Usage characteristics**

Maximum operating temperature	105 °C
Minimum operating temperature	-50 °C
RoHS compliant	Yes