



Country Ref.: Etude 133496

CONTACT

Market information
industryprojects.business@lynxgroup.com

International Designation:

108 channels 38 AWG coax cable

Ultrasound cable assemblies

STANDARDS

Product 448-010-3-10; Nexans specification

Characteristics

Very flexible cable with an extremely good mechanical behaviour.
Withstands miscellaneous sterilisation processes.

CONSTRUCTION

1- CORE (A)

AWG 38 silver plated copper wire.

FEP insulation

Diameter : 0.30 +/- 0.02 mm

AWG 48 silver plated copper helicoidal screen

Nominal diameter : 0.36 mm

FEP jacket

Diameter : 0.46 +/- 0.03 mm

2- CORE (B)

8 Cores (A) twisted.

Nominal diameter : 1.46 mm

ASSEMBLY

13 Cores (B) + 4 Cores (A) twisted

3- PTFE Tape

Nominal diameter : 6.37 mm

4- SHIELD

AWG 40 tin plated copper braid.

85% min coverage.

Nominal diameter : 6.73 mm

6- JACKET

Medical Polyurethane

Nom. Diameter : 7.85 mm

Max. Diameter : 8.00 mm

Main Characteristics

Minimum bending radius : 5 x Overall diameter.



Cable flexibility
Flexible



Maximum operating temperature
85 °C



Minimum operating temperature
-30 °C



RoHS compliant
Yes

CHARACTERISTICS**Construction characteristics**

Construction type	Shielded and sheathed
Conductor shape	Single wired
Conductor material	Silver coated copper
Insulation	FEP

Dimensional characteristics

Approximate weight	93 g/m
Outer Diameter	7.85 mm

Electrical characteristics

Operating voltage	24 V
-------------------	------

Mechanical characteristics

Cable flexibility	Flexible
-------------------	----------

Usage characteristics

Maximum operating temperature	85 °C
Minimum operating temperature	-30 °C
RoHS compliant	Yes