



Country Ref.: Etude 133606

### CONTACT

Market information  
industryprojects.business@lynxeogroup.com

### International Designation:

2 Shielded Pairs 32 AWG

Very flexible cable with an extremely good mechanical behaviour.  
Withstands miscellaneous sterilisation processes.

## STANDARDS

Product Nexans specification

### 1- CORE (A)

#### Core (Z)

AWG 32 stranded Silver plated copper conductor.

FEP insulation.

Diameter : 0.58 +/- 0.03 mm

Assembly 2 Cores (Z)

Nominal diameter : 1.16 mm

AWG40 Tin plated copper spiral shield.

90% min. coverage

PTFE tape

Nominal diameter : 1.43 mm

### Assembly

2 Cores (A) twisted.

Nominal diameter : 2.86 mm

### 2- JACKET

Medical PVC

Nom. Diameter : 4.00 mm

Max. Diameter : 4.20 mm

### Main Characteristics

Minimum bending radius : 5 x Overall diameter.



Cable flexibility  
Very flexible



Maximum operating temperature  
60 °C



Minimum operating temperature  
-20 °C



RoHS compliant  
Yes

**CHARACTERISTICS****Construction characteristics**

Construction type	Shielded and sheathed
Conductor shape	Multi stranded
Conductor material	Silver coated copper
Insulation	FEP

**Dimensional characteristics**

Approximate weight	17 g/m
Outer Diameter	4.1 mm

**Electrical characteristics**

Operating voltage	250 V
-------------------	-------

**Mechanical characteristics**

Cable flexibility	Very flexible
-------------------	---------------

**Usage characteristics**

Maximum operating temperature	60 °C
Minimum operating temperature	-20 °C
RoHS compliant	Yes