



Country Ref.: Etude 133478

## CONTACT

Market information  
industryprojects.business@lynxegroup.com

### International Designation:

28 AWG twisted QUAD

### USB 2.0 high speed

Very flexible cable with an extremely good mechanical behaviour.  
Withstands miscellaneous sterilisation process.

## STANDARDS

### Product Nexans specification

#### CORE A

AWG 28 stranded silver plated copper alloy conductor.  
MFA insulation.  
Diameter : 0.75 +/- 0.05 mm.

#### Assembly

4 Cores (A) twisted.

PTFE tape.

#### CORE B

14 x 0.08 mm Silver plated copper alloy.

#### SHIELD

AWG 40 Silver plated copper alloy braid  
95% min. coverage.

PTFE tape.

#### Medical Polyurethane Jacket

Diameter : 3.30 +/- 0.10 mm.

### Mechanical performances

Minimum static bending radius : 5 x Overall diameter.



Cable flexibility  
Very flexible



Maximum operating temperature  
85 °C



Minimum operating temperature  
-30 °C

**CHARACTERISTICS****Construction characteristics**

Conductor material	Silvered copper
Conductor shape	Multi stranded
Construction type	Shielded and sheathed
Insulation	Fluor polymer

**Dimensional characteristics**

Wire diameter	0.75 mm
Outer Diameter	3.3 mm
Maximum outer diameter	3.4 mm
Approximate weight	19 g/m

**Electrical characteristics**

Operating voltage	24 V
-------------------	------

**Mechanical characteristics**

Cable flexibility	Very flexible
-------------------	---------------

**Usage characteristics**

Maximum operating temperature	85 °C
Minimum operating temperature	-30 °C
Mechanical Resistance	Good mechanical resistance