



Reference: 10135095  
EAN 13: 3427580321368

### CONTACT

Market information  
industryprojects.business@lynxéogroup.com

- Instrumentation cables 170/300 V
- Overall Screen (OS)
- Oil resistant

### STANDARDS

Test IEC 60331; IEC 60332-3-22 Cat.A

### APPLICATIONS

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control**. They are well adapted to **underground use in industrial application where chemical and mechanical protections are needed (refinery areas, chemical plant...)**. They maintain circuit integrity when exposed to fire.

### Design

#### Conductor:

Stranded bare copper class 2

#### Insulation:

Silicone rubber (Sil)

#### Overall screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

#### Bedding (inner sheath):

Low Smoke Zero Halogen (LSZH)

Colour: black

#### Armour:

Galvanized steel wires (SWA)

#### Outer sheath:

Polyvinyl chloride (PVC)

Colour: black

Other colour on request.

### Core identification

Pair: white - black

Quad: white - black - red - blue (2 pair cables assembled as a quad)

White core printed with pair number



Rated Voltage U<sub>o</sub>/U<sub>l</sub>  
(Um)  
170/300V



Mechanical  
resistance to  
impacts  
Good



Fire resistance  
IEC 60331



Fire retardant  
EN IEC 60332-3-22  
(cat A)  
Oil resistance  
Yes



Electro magnetic  
interference  
resistance  
Yes

Operating temp.  
-20 ... 60 °C



Max. conductor  
temp. in service  
90 °C

### Marking

NEXANS 279 SIL/OA.SCR/LSZH/SWA/PVC 170/300V Nber of pairs & cross-section  
Cu IEC 60331 IEC 60332-3-22(A) MM YYYY Manufacturing number + metric marking

### Standards

All drawings, designs, specifications, plans and particulars of weights, size and dimensions  
conforming to EN 50288-7 (Design guide lines) documentation of Lynxéo is indicative only and shall not be  
binding on Lynxéo or be treated as constituting a representation on the part of Lynxéo.

### CHARACTERISTICS

#### Construction characteristics

Conductor material	Bare copper
Type of conductor	Stranded, class 2
Insulation	Silicone rubber
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Inner sheath	Low smoke, zero halogen thermoplastic compound
Armour type	Galvanized steel wires
Outer sheath	PVC
Protection	Yes

#### Dimensional characteristics

Number of pairs	1
Conductor cross-section	1 mm <sup>2</sup>
Conductor diameter	1.28 mm
Diameter over insulation	2.44 mm
Diameter over inner sheath	7 mm
Diameter over armour	8.8 mm
Minimum outer diameter	10.5 mm
Maximum outer diameter	12.2 mm
Approximate weight	254 kg/km

#### Electrical characteristics

Rated Voltage U <sub>o</sub> /U (Um)	170/300V
--------------------------------------	----------

#### Mechanical characteristics

Mechanical resistance to impacts	Good
----------------------------------	------

#### Usage characteristics

Fire resistant	IEC 60331
Fire retardant	EN IEC 60332-3-22 (cat A)
Oil resistance	Yes
Electro magnetic interference resistance	Yes
Operating temperature, range	-20 ... 60 °C
Max. conductor temperature in service	90 °C
Standard	EN

### SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:



Rated Voltage U<sub>o</sub>/U (Um)  
170/300V



Mechanical resistance to impacts  
Good



Fire resistant  
IEC 60331



Fire retardant  
EN IEC 60332-3-22 (cat A)



Oil resistance  
Yes



Electro magnetic interference resistance  
Yes



Operating temp.  
-20 ... 60 °C



Max. conductor temp. in service  
90 °C

15 x outer diameter  
To be doubled during laying operations

Tinned copper conductors available on request



Rated Voltage  $U_0/U$   
(Um)  
**170/300V**



Mechanical  
resistance to  
impacts  
**Good**



Fire resistant  
**IEC 60331**



Fire retardant  
**EN IEC 60332-3-22**  
(cat A)



Oil resistance  
**Yes**



Electro magnetic  
interference  
resistance  
**Yes**



Operating temp.  
**-20 ... 60 °C**



Max. conductor  
temp. in service  
**90 °C**