



Reference: 10135236  
EAN 13: 3427580322778

#### CONTACT

Market information  
industryprojects.business@lynx<sup>eo</sup>.group.com

- Instrumentation cables 170/300 V
- With lead cover (LC)
- Individual & Overall Screen (IOS)
- **Aliphatic and aromatic hydrocarbons resistant**

#### STANDARDS

Ensayo IEC 60331; IEC 60332-3-22 Cat.A

#### APPLICATIONS

These instrumentation and communication cables are used to **transmit analogue or digital signals in measurement and process control**. They are well adapted to **underground use** in industrial applications, in moist areas, where **hydrocarbon and mechanical protection are needed**. The **lead cover brings an enhanced resistance to aromatics hydrocarbons**. The **individual screening of each pair limits the consequence of crosstalk**. They maintain circuit integrity when exposed to fire.

#### Design

##### Conductor:

Stranded bare copper class 2

##### Insulation:

Silicone rubber (Sil)

##### Individual screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

Polyester tape

##### Overall screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

##### Inner sheath:

Low Smoke Zero Halogen (LSZH)

Colour: black

##### Lead sheath:

##### Bedding (intermediate sheath):

Polyvinyl chloride (PVC)

Colour: black

Resistente al fuego  
IEC 60331

##### Armour:

No propagador del incendio  
EN IEC 60332-3-22  
(cat A)

Resistencia química  
**Aliphatic and aromatic hydrocarbons resistant**

Resistencia a interferencias electromagnéticas  
SI

Temp. ambiente de utilización  
-20 ... 60 °C

Max.conductor temp.in service  
90 °C

Galvanized steel wires (SWA)

##### Outer sheath:

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Lynx<sup>eo</sup> is indicative only and shall not be binding on Lynx<sup>eo</sup> or be treated as constituting a representation on the part of Lynx<sup>eo</sup>.  
Colour: black

Other colour on request.



Tensión nominal de servicio Uo/U  
170/300V



Resistencia mecánica a impactos  
Buena



Resistente al fuego  
IEC 60331

##### Armour:

No propagador del incendio  
EN IEC 60332-3-22  
(cat A)

Resistencia química  
**Aliphatic and aromatic hydrocarbons resistant**

Resistencia a interferencias electromagnéticas  
SI

Temp. ambiente de utilización  
-20 ... 60 °C

Max.conductor temp.in service  
90 °C

Galvanized steel wires (SWA)

##### Outer sheath:

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Lynx<sup>eo</sup> is indicative only and shall not be binding on Lynx<sup>eo</sup> or be treated as constituting a representation on the part of Lynx<sup>eo</sup>.  
Colour: black

Other colour on request.

### CHARACTERISTICS

#### Características de construcción

Material del conductor	Cobre desnudo
Type of conductor	Stranded, class 2
Aislamiento	Silicone rubber
Individual screen	Tinned copper drain wire + aluminium/polyester tape
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Cubierta interior	Low smoke, zero halogen thermoplastic compound
Lead Sheath	Yes
Intermediate sheath	PVC
Tipo de armadura	Alambres de acero galvanizado
Cubierta exterior	PVC
Protección	Yes

#### Características dimensionales

Número de pares	20
Sección del conductor	0,5 mm <sup>2</sup>
Diámetro del conductor	0,9 mm
Diámetro sobre aislamiento	2,06 mm
Diameter over inner sheath	23,2 mm
Diameter over lead sheath	25,8 mm
Diameter over intermediate sheath	28,2 mm
Diameter over armour	30,7 mm
Diámetro exterior mínimo	31,1 mm
Diámetro exterior máximo	36,2 mm
Peso aproximado	2810 kg/km

#### Características eléctricas

Tensión nominal de servicio U <sub>0</sub> /U	170/300V
---	----------

#### Características mecánicas

Resistencia mecánica a impactos	Buena
---------------------------------	-------

#### Características de uso

Resistente al fuego	IEC 60331
No propagador del incendio	EN IEC 60332-3-22 (cat A)
Resistencia química	Aliphatic and aromatic hydrocarbons resistant
Resistencia a interferencias electromagnéticas	Si
Temperatura ambiente de utilización (rango)	-20 ... 60 °C
Temperatura máxima del conductor	90 °C
Standard	EN



Tensión nominal de servicio U<sub>0</sub>/U  
170/300V



Resistencia mecánica a impactos  
Buena



Resistente al fuego  
IEC 60331



No propagador del incendio  
EN IEC 60332-3-22 (cat A)



Resistencia química  
Aliphatic and aromatic hydrocarbons resistant



Resistencia a interferencias electromagnéticas  
Si



Temp. ambiente de utilización  
-20 ... 60 °C



Max. conductor temp. in service  
90 °C

**SELLING AND DELIVERY INFORMATION**

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) on request.

Minimum bending radius:

10 x outer diameter  
 To be doubled during laying operations

Tinned copper conductors available on request



Tensión nominal de servicio Uo/U  
**170/300V**



Resistencia mecánica a impactos  
**Buena**



Resistente al fuego  
**IEC 60331**



No propagador del incendio  
**EN IEC 60332-3-22 (cat A)**



Resistencia química  
**Aliphatic and aromatic hydrocarbons resistant**



Resistencia a interferencias electromagnéticas  
**SI**



Temp. ambiente de utilización  
**-20 ... 60 °C**



Max. conductor temp. in service  
**90 °C**