



Reference: 10176316
EAN 13: 3427580464812

CONTACT

Market information
industryprojects.business@lynx^{eo}.group.com

- CST 74C068
- Quality insurance according to RCC - E
- Zero halogen (SH)
- Control cables 0.3/0.5 (0.6) kV
- Cables installed inside of the containment area (K1)
- Overall Screen (EG)
- Unarmoured (NA)

STANDARDS

Product IEC 60228

Test a; IEC 60332 - 3 - 23; IEC 60754 - 1; IEC 61034 - 2; NF C32 - 070/C1

APPLICATIONS

These control cables allow connection to a variety of industrial equipment from control room. Many of them require anti - inductive screen (EMI).

CONSTRUCTION

Conductor:

- Stranded (class 2) or flexible (class 5) plain copper

Insulation:

- Zero halogen (SH), cross - linked

Assembling:

- Polyester tape (optional)

Inner sheath:

- Low smoke, zero halogen (LSZH)

Overall screen:

- Copper wire braid (CWB) R 80%

Outer sheath:

- Low smoke, zero halogen (LSZH)
- Colour: Grey

Core identification

Black cores printed with white numbers
Optional: with G/Y core

Marking

LYNXEO 279 Nber of cores & cross - section Cu EG CST 74 C 068 K1 SH 0.3/0.5 (0.6) kV YYYY Manufacturing number + metric marking



Halogen free
IEC 60754 - 1; IEC 60754 - 2



Uo/U
(Um)
0.3/0.5(0.6)kV



Operating temp.
- 20 ... 60 ° C



Fire retardant
NF C 32070 C1;
IEC 60332 - 3 - 24
(cat.B)



Electro magnetic
interference
resistance
Yes



Life cycle 60years
Yes



Radiation
resistant
Yes

CHARACTERISTICS

	2 ()
	LSZH Copper Braid
Halogen free	IEC 60754 - 1; IEC 60754 - 2
	1 mm ² 9
	1.3 mm
Diameter over insulation	2.5 mm
Diameter over inner sheath	11.1 mm
Diameter over screen	12.1 mm
Minimum outer diameter	13.7 mm
Maximum outer diameter	16.5 mm
()	400 kg/km
20 ° C DC	18.1 Ohm/km
Maximum DC resistance of the conductor at 90 ° C	23.000 Ohm/km
Reactance at 50 Hz	0.1 Ohm/km
Short Circuit Current 0,3 s Max	0.26 kA
Short Circuit Current 1 s Max	0.14 kA
Impedance at 50 Hz	18.1 Ohm
Voltage Drop	32.0 V/A.km
Calorific Power	4.2 MJ/m
U _o /U (U _m)	0.3/0.5(0.6)kV
操作度范	- 20 ... 60 ° C
	-
Fire retardant	NF C 32070 C1; IEC 60332 - 3 - 24 (cat.B)
Electro magnetic interference resistance	Yes
Life cycle 60years	Yes
Radiation resistant	Yes
Loss of coolant accident resistant	Yes
U.V resistance	Yes
Max. conductor temperature in service	90 ° C
Nuclear Classification	Class 1 E LOCA /K1

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations