



Reference: 10192976
EAN 13: 3427580555275

CONTACT

Market information
 industryprojects.business@lynxéogroup.com

- Instrumentation cables 170/300 V
- Overall Screen (OS)
- **Oil resistant**

STANDARDS

Test IEC 60332-3-22 Cat.A

APPLICATIONS

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control where chemicals may be present.**

Design

Conductor:

Stranded bare copper class 2

Insulation:

Cross-linked polyethylene (XLPE)

Overall screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

Outer sheath:

Polyvinyl chloride (PVC).

Colour: black.

Other colour on request.

Core identification

Pair: white - black

Quad: white - black - red - blue (2 pair cables assembled as a quad)

White core printed with pair number

Marking

NEXANS 279 XLPE/OA.SCR/PVC 170/300V Nber of pairs & cross-section Cu IEC 60332-3-22(A) MM YYYY Manufacturing number + metric marking

Standards

EN 50288-7 (Design guide-lines)



Tensione nominale U₀/U
 (Um)
 170/300V



Fuoco ritardante
 EN IEC 60332-3-22 (cat
 A)



Resistenza all'olio
 Sì



Resistenza ad interferenza
 elettromagnetica
 Sì



Temperatura Operativa
 -20 ... 60 °C



Temp. max di servizio del
 conduttore
 90 °C

CHARACTERISTICS

Caratteristiche costruttive

Materiale del conduttore	Rame nudo
Tipo di conduttore	A trefoli, Classe 2
Isolamento	XLPE (polietilene reticolato)
Schermo Collettivo	Filo di rame stagnato + Nastro Alluminio / Polyestere
Guaina esterna	PVC
Protezione	No

Caratteristiche dimensionali

Numero di coppie	5
Sezione del conduttore del cavo	1,5 mm ²
Diametro nominale sull'isolante	2,16 mm
Diametro esterno max	15,6 mm
Diametro esterno min	14,2 mm
Diametro nominale del conduttore del cavo	1,5 mm
Peso approssimativo del cavo	277 kg/km

Caratteristiche elettriche

Tensione nominale U _o /U (Um)	170/300V
--	----------

Caratteristiche d'utilizzo

Fuoco ritardante	EN IEC 60332-3-22 (cat A)
Resistenza all'olio	Si
Resistenza ad interferenza elettromagnetica	Si
Temperatura Operativa	-20 ... 60 °C
Temperatura massima di servizio del conduttore	90 °C
Standard	EN

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

Tinned copper conductors available on request



Tensione nominale U_o/U (Um)
170/300V



Fuoco ritardante
EN IEC 60332-3-22 (cat A)



Resistenza all'olio
Si



Resistenza ad interferenza elettromagnetica
Si



Temperatura Operativa
-20 ... 60 °C



Temp. max di servizio del conduttore
90 °C