



**Reference:** 10192997  
**EAN 13:** 3427580555480

### CONTACT

Market information  
 industryprojects.business@lynxéogroup.com

- Instrumentation cables 170/300 V
- Overall Screen (OS)
- **Oil resistant**

### STANDARDS

**Ensayo** IEC 60332-3-22 Cat.A

### APPLICATIONS

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control where chemicals may be present.**

### Design

Conductor:

Stranded bare copper class 2

Insulation:

Cross-linked polyethylene (XLPE)

Overall screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

Outer sheath:

Polyvinyl chloride (PVC).

Colour: black.

Other colour on request.

### Core identification

Pair: white - black

Quad: white - black - red - blue (2 pair cables assembled as a quad)

White core printed with pair number

### Marking

NEXANS 279 XLPE/OA.SCR/PVC 170/300V Nber of pairs & cross-section Cu IEC 60332-3-22(A) MM YYYY Manufacturing number + metric marking

### Standards

EN 50288-7 (Design guide-lines)



Tensión nominal de servicio  
 Uo/U  
 170/300V



No propagador del incendio  
 EN IEC 60332-3-22 (cat A)



Resistencia a aceites  
 Sí



Resistencia a interferencias electromagnéticas  
 Sí



Temp. ambiente de utilización  
 -20 ... 60 °C



Max.conductor temp.in service  
 90 °C

### CHARACTERISTICS

#### Características de construcción

Material del conductor	Cobre desnudo
Type of conductor	Stranded, class 2
Aislamiento	XLPE
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Cubierta exterior	PVC
Protección	no

#### Características dimensionales

Número de pares	20
Sección del conductor	2,5 mm <sup>2</sup>
Diámetro sobre aislamiento	2,57 mm
Diámetro del conductor	1,91 mm
Diámetro exterior máximo	30,2 mm
Diámetro exterior mínimo	27,4 mm
Peso aproximado	1210 kg/km

#### Características eléctricas

Tensión nominal de servicio U <sub>0</sub> /U	170/300V
---	----------

#### Características de uso

No propagador del incendio	EN IEC 60332-3-22 (cat A)
Resistencia a aceites	Sí
Resistencia a interferencias electromagnéticas	Sí
Temperatura ambiente de utilización (rango)	-20 ... 60 °C
Temperatura máxima del conductor	90 °C
Standard	EN

### SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:

10 x outer diameter  
To be doubled during laying operations

Tinned copper conductors available on request



Tensión nominal de servicio  
U<sub>0</sub>/U  
170/300V



No propagador del incendio  
EN IEC 60332-3-22 (cat A)



Resistencia a aceites  
Sí



Resistencia a interferencias  
electromagnéticas  
Sí



Temp. ambiente de  
utilización  
-20 ... 60 °C



Max. conductor temp.in  
service  
90 °C