



Reference: 10193083
EAN 13: 3427580556340

CONTACT

Market information
 industryprojects.business@lynxogroup.com

- Instrumentation cables 170/300 V
- Individual & Overall Screen (IOS)
- **Oil resistant**

STANDARDS

Tests IEC 60332-3-22 Cat.A

APPLICATIONS

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control where chemicals may be present. The individual screening of each pair limits the consequence of crosstalk.**

Design

Conductor:

Stranded bare copper class 2

Insulation:

Cross-linked polyethylene (XLPE)

Individual screen:

Polyester tape

Tinned copper drain wire,

Aluminium backed polyester tape

Polyester tape

Overall screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

Outer sheath:

Polyvinyl chloride (PVC).

Colour: black.

Other colour on request.

Core identification

Pair: white - black

White core printed with pair number



Nennspannung Uo/U
 170/300V



Flammwidrig
 EN IEC 60332-3-22 (Cat.A)



Marking

NEXANS 279 XLPE/IND+OA-SCR/PVC 170/300V Nber of pairs & cross-section Cu IEC
 60332-3-22(A) MM YYYY Manufacturing number °C metric marking



Standards

EN 50288-7 (Design guide-lines)

Alle Zeichnungen, Entwürfe, Spezifikationen, Pläne und Angaben zu Gewichten, Größen und Abmessungen in der technischen oder kommerziellen Dokumentation von Lynxéo sind nur indikativ und sind für Lynxéo nicht verbindlich und dürfen nicht als Zusicherung seitens Lynxéo betrachtet werden

CHARACTERISTICS

Konstruktionsmerkmale

Leitermaterial	Kupfer, blank
Leitertyp	Stranded, class 2
Isolierung	VPE (vernetztes Polyethylen)
Einzel geschirmt	Tinned copper drain wire + aluminium/polyester tape
Gemeinsamer Schirm	Tinned copper drain wire + aluminium/polyester tape
Außenmantel	PVC
Schutz	Nein

Abmessungsmerkmale

Anzahl Paare	5
Leiterquerschnitt	0,5 mm ²
Leiterdurchmesser	0,9 mm
Durchmesser über Isolierung	1,38 mm
Außendurchmesser Mindestwert	11,0 mm
Maximaler Außendurchmesser	12,1 mm
Nettogewicht ca.	170 kg/km

Elektrische Eigenschaften

Nennspannung U ₀ /U	170/300V
--------------------------------	----------

Anwendungsmerkmale

Flammwidrig	EN IEC 60332-3-22 (cat A)
Ölbeständig	Ja
Elektromagnetisch geschirmt	Ja
Betriebstemperatur	-20 ... 60 °C
Max. Betriebstemperatur am Leiter	90 °C
Standard	EN

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

Tinned copper conductors available on request



Nennspannung U₀/U
170/300V



Flammwidrig
EN IEC 60332-3-22 (cat A)



Ölbeständig
Ja



Elektromagnetisch geschirmt
Ja



Betriebstemp.
-20 ... 60 °C



Max. Betriebstemp. am Leiter
90 °C