



## POWER & CONTROL cables without screen

### STANDARDS

Installation IEC 60092 - 3; IEC 60092 - 350

Test a; IEC 60332 - 3 Cat.A; IEC 60754 - 1; IEC 61034

International IEC 60298

### APPLICATIONS

Reference: 10200170  
 EAN 13: 3427650115316

### CONTACT

Market information  
 industryprojects.business@lyn  
 xeogroup.com



Conductor flexibility

2



Halogen free  
 IEC 60754 - 1



U<sub>0</sub>/U  
 (Um)  
 0.6/ 1 (1.2) kV



Fire retardant  
 EN IEC  
 60332 - 3 - 22 (cat  
 A)



IEC 60332 - 1



IEC 61034



Gases corrosivity  
 IEC 60754 - 2



Operating temp.  
 -30 ... 80 °C

## CHARACTERISTICS

Conductor flexibility		2
	XLPE(가 )	
Conductor shape		
Material of filler / inner sheath		
Halogen free		IEC 60754 - 1
Sheath colour		
With Green/Yellow core		
		5
		2.5 mm <sup>2</sup>
Nominal outer diameter		11.1 mm
Minimum outer diameter		10.7 mm
Maximum outer diameter		12.2 mm
( )		188 kg/km
Permissible short circuit current		0.4 kA
Permissible current rating in open air		21 A
20 ° C	DC	7.41 Ohm/km
U <sub>o</sub> /U (U <sub>m</sub> )		0.6/ 1 (1.2) kV
Fire retardant	EN IEC 60332 - 3 - 22 (cat A)	
	IEC 60332 - 1	
	IEC 61034	
Gases corrosivity		IEC 60754 - 2
操作度范		- 30 ... 80 ° C
Max. conductor temperature in service		90 ° C

## OTHER CHARACTERISTICS

Test Voltage  
 AC between cores.....  
 3.5 kV AC

Minimum bending radius for fixed installations MPRX®  
 • cable diameter 25 mm..... 4 x outer diameter  
 • cable diameter > 25 mm..... 6 x outer diameter

Minimum bending radius for fixed installations MPRX® FLEXISHIP®..... 4 x outer diameter