



Reference: 10213053
EAN 13: 3427580629693

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

- CST 74C068
- Quality insurance according to RCC - E
- Zero halogen (SH)
- Control cables 0.3/0.5 (0.6) kV
- Cables installed inside of the containment area (K2)
- Overall screened (EG)
- Unarmoured (NA)

STANDARDS

Product IEC 60228

Test IEC 60332 - 3 - 23; IEC 60754 - 1; IEC 61034 - 2; NF C32 - 070/C1

APPLICATIONS

These control cables allow connection to a variety of industrial equipment from control room. Many of them require anti - inductive screen (EMI).

CONSTRUCTION

Conductor:

- Stranded (class 2) or flexible (class 5) plain copper

Insulation:

- Zero halogen (SH), cross - linked

Assembling:

- Polyester tape (optional)

Inner sheath:

- Low smoke, zero halogen (LSZH)
- Colour: grey

Screen:

- Copper wire braid (CWB) R 80 %

Outer sheath:

- Low smoke, zero halogen (LSZH)
- Colour: grey

Core identification

Black cores printed with white numbers
Optional: with G/Y core.

Marking

LYNXEO 279 Nber of cores & cross - section Cu EG CST 74 C 068 K2 SH
0.3/0.5 (0.6) kV YYYY Manufacturing number + metric marking



Halogen free
IEC 60754 - 1; IEC
60754 - 2



Operating temp.
- 20 ... 60 ° C



IEC 61034 - 2



Fire retardant
NF C 32070 C1;
IEC 60332 - 3 - 24
(cat.B)



Electro magnetic
interference
resistance
Yes



U.V resistance
Yes



Life cycle 60years
Yes



Radiation
resistant
Yes

CHARACTERISTICS

	2 ()	
		-
		Bare copper braid
Halogen free		IEC 60754 - 1; IEC 60754 - 2
		0.5 mm ²
		48
		0.9 mm
Diameter over insulation		2.2 mm
Diameter over inner sheath		19.8 mm
Diameter over screen		21.3 mm
Minimum outer diameter		23.4 mm
Maximum outer diameter		27.4 mm
()		1005 kg/km
20 ° C	DC	36 Ohm/km
Maximum DC resistance of the conductor at 90 ° C		45.900 Ohm/km
Reactance at 50 Hz		0.112 Ohm/km
Short Circuit Current 0,3 s Max		0.13 kA
Short Circuit Current 1 s Max		0.07 kA
Impedance at 50 Hz		36 Ohm
Voltage Drop		73.6 V/A.km
Calorific Power		6.9 MJ/m
操作度范		- 20 ... 60 ° C
		IEC 61034 - 2
Fire retardant		NF C 32070 C1; IEC 60332 - 3 - 24 (cat.B)
Electro magnetic interference resistance		Yes
U.V resistance		Yes
Life cycle 60years		Yes
Radiation resistant		Yes
Max. conductor temperature in service		90 ° C
Nuclear Classification		K2

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

Marking

LYNXEO 279 Nber of cores & cross - section Cu EG CST 74 C 068 K2 SH 0.3/0.5 (0.6)
kV YYYY Manufacturing number + metric marking