



Reference: 10216539
EAN 13: 3427580637513

CONTACT

Market information
 industryprojects.business@lynxgroup.com

- Medium voltage cables 6/6 (7.2) kV
- CST 74C068
- Zero halogen (SH)
- **Cables installed outside of the containment area (K3)**
- Unarmoured (NA)

STANDARDS

Produkt IEC 60228; IEC 60502-2

Tests IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

APPLICATIONS

These medium voltage cables are used for medium voltage power supply,

DESIGN

Design

Conductor:

Stranded bare copper or aluminium (class 2)

Screen:

Semi-conductor

Insulation:

Ethylene Propylene Rubber (EPR)

Assembling sheath:

Halogen free

Inner sheath:

Halogen free

Screen:

Semi-conductor

Copper tape

Outer sheath:

Low smoke, zero halogen (LSZH)

Colour: Black

Core identification

3x: natural cores printed with black numbers



Halogenfrei
 IEC 60754-1



Nennspannung U_o/U
 6/6(7.2) kV



Marking

Flammwidrig
 NF C 32070 C1; IEC 60332-3-24
 (cat.B)



Rauchdichte
 EN/IEC 61034-2



Betriebstemp.
 -20 ~ 60 °C



Max. Betriebstemp. am
 Leiter

LYN^{EO} 279 Nbr of cores & cross-section Cu/Al CST 74 50 068 00 K3 SH 6/6(7.2) kV YYY YYY Manufacturing number + metric marking

STANDARD

Alle Zeichnungen, Entwürfe, Spezifikationen, Pläne und Angaben zu Gewichten, Größen und Abmessungen in der technischen oder kommerziellen Dokumentation von Lynx^{eo} sind nur indikativ und sind für Lynx^{eo} nicht verbindlich und dürfen nicht als Zusicherung seitens Lynx^{eo} betrachtet werden

IEC 60332-3-23(B)

CHARACTERISTICS

Konstruktionsmerkmale

Leitermaterial	Aluminium
Leitertyp	Stranded, class 2
Isolierung	Halogen-free
Außenmantel	Halogen-free
Halogenfrei	IEC 60754-1

Abmessungsmerkmale

Leiterquerschnitt	240 mm ²
Aderanzahl	3
Außendurchmesser Mindestwert	66,9 mm
Maximaler Außendurchmesser	73,8 mm
Nettogewicht ca.	6481 kg/km
Diameter over screen	62,2 mm

Elektrische Eigenschaften

Nennspannung U _o /U	6/6(7.2) kV
--------------------------------	-------------

Anwendungsmerkmale

Flammwidrig	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Rauchdichte	EN/IEC 61034-2
Betriebstemperatur	-20 ... 60 °C
Max. Betriebstemperatur am Leiter	90 °C
Nuclear Classification	Class 1 E Non LOCA/K3

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

8 x outer diameter
To be doubled during laying operations



Halogenfrei
IEC 60754-1



Nennspannung U_o/U
6/6(7.2) kV



Flammwidrig
NF C 32070 C1; IEC 60332-3-24
(cat.B)



Rauchdichte
EN/IEC 61034-2



Betriebstemp.
-20 ... 60 °C



Max. Betriebstemp. am
Leiter
90 °C