



Reference: 10260491
EAN 13: 3427580716706

CONTACT

Market information
 industryprojects.business@lynxgroup.com

- CST 74C068
- Quality insurance according to RCC-E
- Zero halogen (SH)
- Control cables 0.3/0.5 (0.6) kV
- **Cables installed inside of the containment area (K2)**
- Overall screened (EG)
- Unarmoured (NA)

STANDARDS

Producto IEC 60228

Ensayo IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

APPLICATIONS

These control cables allow connection to a variety of industrial equipment from control room. Many of them require anti-inductive screen (EMI).

CONSTRUCTION

Conductor:

- Stranded (class 2) or flexible (class 5) plain copper

Insulation:

- Zero halogen (SH), cross-linked

Assembling:

- Polyester tape (optional)

Inner sheath:

- Low smoke, zero halogen (LSZH)
- Colour: grey

Screen:

- Copper wire braid (CWB) R ≥ 80 %

Outer sheath:

- Low smoke, zero halogen (LSZH)
- Colour: grey

Core identification

Black cores printed with white numbers
 Optional: with G/Y core.

Marking

LYNXEO 279 Nber of cores & cross-section Cu EG CST 74 C 068 K2 SH 0.3/0.5 (0.6) kV YYYY Manufacturing number + metric marking



Libre de halógenos
 IEC 60754-1; IEC 60754-2



Temp. ambiente de utilización
 -20 ... 60 °C



Densidad de los humos
 IEC 61034-2



No propagador del incendio
 NF C 32070 C1;
 IEC 60332-3-24 (cat.B)



Resistencia a interferencias electromagnéticas
 SI



Resistencia a radiaciones ultravioletas
 SI



Life cycle 60years
 Yes



Radiation resistant
 Yes

CHARACTERISTICS**Características de construcción**

Material del conductor	Plain copper
Type of conductor	Stranded, class 2
Aislamiento	Halogen-free
Cubierta interior	-
Pantalla	Bare copper braid
Cubierta exterior	LSZH
Libre de halógenos	IEC 60754-1; IEC 60754-2

Características dimensionales

Sección del conductor	1 mm ²
Número de conductores	12
Diámetro del conductor	1,3 mm
Diámetro sobre aislamiento	2,4 mm
Diameter over inner sheath	12,5 mm
Diameter over screen	13,5 mm
Diámetro exterior mínimo	15,3 mm
Diámetro exterior máximo	17,5 mm
Peso aproximado	475 kg/km

Características eléctricas

Resistencia máxima del conductor en CC a 20° C	18,1 Ohm/km
Maximum DC resistance of the conductor at 90°C	23,000 Ohm/km
Reactance at 50 Hz	0,1 Ohm/km
Short Circuit Current 0,3 s Max	0,26 kA
Short Circuit Current 1 s Max	0,14 kA
Impedance at 50 Hz	18,1 Ohm
Voltage Drop	36,9 V/A.km
Calorific Power	3,4 MJ/m

Características de uso

Temperatura ambiente de utilización (rango)	-20 ... 60 °C
Densidad de los humos	IEC 61034-2
No propagador del incendio	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Resistencia a interferencias electromagnéticas	Sí
Resistencia a radiaciones ultravioletas	Sí
Life cycle 60years	Yes
Radiation resistant	Yes
Temperatura máxima del conductor	90 °C
Nuclear Classification	K2

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

Marking

LYNXEO 279 Nber of cores & cross-section Cu EG CST 74 C 068 K2 SH 0.3/0.5 (0.6) kV YYYY Manufacturing number + metric marking