



**Reference:** 10269286  
**EAN 13:** 3427580821028

### CONTACT

Market information  
 industryprojects.business@lynxeogroup.com

## Fire Resistant Armoured cables CR1-C1-C2 RATP Specification K27

### STANDARDS

**Product** IEC 60228; NF C32-310  
**Test** NF C32-070/C1; NF C32-070/C2

### DESIGN

- 1. Conductor**  
 Bare copper - Solid class 1 for cross sections < 4mm<sup>2</sup>  
 Stranded class 2 for cross section ≥ 4mm<sup>2</sup>
- 2. Insulation**  
 Mica tape + Silicone rubber
- 3. Assembly**
- 4. Inner sheath**  
 Halogen free Polyolefin
- 5. Armour**  
 Stainless steel tapes
- 6. Sheath**  
 Halogen free Polyolefin  
 Colour: orange

### Core identification

- 2x: brown - blue
- 3x: brown - black - grey (brown - black - blue if the conductor cross-section is 1.5 or 2.5mm<sup>2</sup>)
- 3G: brown - blue - green/yellow
- 4x: brown - black - grey - blue
- 4G: brown - black - grey - green/yellow
- 5x: black cores with printed numbers
- 5G: blue - brown - black - grey - green/yellow
- 7 cores and above : black cores with printed numbers

### Marking

K27 - 300/500V - Number of cores & cross-section - ARMÉ - MM/YY - LYNXEO 279 - Manufacturing n° + metric marking



Halogen free  
 IEC 60754-1



Mechanical  
 resistance to  
 impacts  
 Good



Fire resistant  
 NF C 32-070 CR1



Fire retardant  
 NFC 32070 C1



Flame retardant  
 NFC 32070 C2



Smoke density  
 IEC 61034-2



Gases corrosivity  
 IEC 60754-2



Operating temp.  
 -20 ... 70 °C

**CHARACTERISTICS****Construction characteristics**

Conductor material	Plain copper
Insulation	Mica tape
Insulating material	Silicone
Armour type	Steel tapes
Inner sheath	Polyolefin
Outer sheath	Halogen free polyolefin
Sheath colour	Orange
Halogen free	IEC 60754-1
Type of conductor	Stranded, class 2
With Green/Yellow core	Yes

**Dimensional characteristics**

Number of cores	5
Conductor cross-section	16 mm <sup>2</sup>
Approximate weight	1700 kg/km
Maximum outer diameter	29.0 mm
Minimum outer diameter	- mm

**Electrical characteristics**

DC permissible current rating	- A
Voltage Drop	- V/A.km

**Mechanical characteristics**

Mechanical resistance to impacts	Good
----------------------------------	------

**Usage characteristics**

Fire resistant	NF C 32-070 CR1
Fire retardant	NFC 32070 C1
Flame retardant	NFC 32070 C2
Smoke density	IEC 61034-2
Gases corrosivity	IEC 60754-2
Operating temperature, range	-20 ... 70 °C
Max. conductor temperature in service	90 °C
Oil resistance	Good
Chemical resistance	Good
Rodent protection	Yes