



**Reference:** 10270788  
**EAN 13:** 3427580734410

**FIRE PERFORMANCE CLASS**



B2ca-s1a,d0,a1

**CONTACT**

Market information  
industryprojects.business@lynxéogroup.com

These cables are intended for fixed power or lighting circuits in tunnels, stations and subway stations. These B2ca cables comply with RATP K20 specifications .

**STANDARDS**

**Produkt** EN 50575; EN 60228

**Installation** NF F 55-625

**APPLICATION**

These cables are used for fixed power or lighting installations in tunnels and underground stations.

**FIRE PERFORMANCE**

- Flame retardant: according to RATP K20 specification
- Fire retardant: according to RATP K20 specification
- Low smoke: according to RATP K20 specification
- Low toxicity: According to RATP K20 specification
- Low corrosivity: According to RATP K20 specification
- Without Halogen : According to RATP K20 specification

**Reaction to fire: B2ca-s1a, d0, a1**

**DESIGN**

- **Conductor:** Bare copper class 1 or 2
- **Insulation:** Cross-linked Polyethylene (XLPE)
- **Assembling:** An inner sheath acting as a filler
- **Outer sheath:** Polyolefin without halogen Colour : black

**Core identification**

According to NF F 55625

2x: black - blue

3x: black - grey - brown

3G: black - blue - green/yellow

4x: black - blue - brown - black

4G: black - blue - brown - green/yellow

5G: black - blue - brown - black - green/yellow

≥ 7 conductors: black cores printed with numbers with or without green/yellow



Halogenfrei  
IEC/EN 60754-1



Flammwidrig  
IEC/EN 60332-1-2



Rauchdichte  
IEC 61034-2 & EN 61034-2



Korrosivität der (Brand-)Gase  
IEC/EN 60754-2



Max. Betriebstemp. am Leiter  
90 °C



Betriebstemp.  
-20 ... 60 °C

## CHARACTERISTICS

### Konstruktionsmerkmale

Leitertyp	Stranded, class 2
Leitermaterial	blank
Isolierung	VPE (vernetztes Polyethylen)
Außenmantel	Halogen free polyolefin
Halogenfrei	IEC/EN 60754-1
Mit grün-gelber Ader	Nein

### Abmessungsmerkmale

Aderanzahl	2
Leiterquerschnitt	4 mm <sup>2</sup>
Außendurchmesser Mindestwert	- mm
Maximaler Außendurchmesser	13,7 mm
Nettogewicht ca.	265 kg/km

### Anwendungsmerkmale

Flammwidrig	IEC/EN 60332-1-2
Rauchdichte	IEC 61034-2 & EN 61034-2
Korrosivität der (Brand-)Gase	IEC/EN 60754-2
Max. Betriebstemperatur am Leiter	90 °C
Betriebstemperatur	-20 ... 60 °C

## COMPLEMENT

### Bending radius

$r = 8 \times \text{maximum outer diameter}$

## SELLING AND DELIVERY INFORMATION

### Marking

750 V cables: 750 - Nber of cores & cross-section - SH - NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 - Manufacturing number DoP:1000648-FRME + metric marking  
1000 V cables: 1000 - Nber of cores & cross-section - SH - NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 - Manufacturing number DoP:1000648-FRME + metric marking