



Reference: 10270838
EAN 13: 3427580734915

FIRE PERFORMANCE CLASS



B2ca-s1a,d0,a1

CONTACT

Market information
industryprojects.business@lynxegroup.com

These cables are intended for fixed power or lighting circuits in tunnels, stations and subway stations. These B2ca cables comply with RATP K20 specifications .

STANDARDS

Product EN 50575; EN 60228

Installation NF F 55-625

APPLICATION

These cables are used for fixed power or lighting installations in tunnels and underground stations.

FIRE PERFORMANCE

- Flame retardant: according to RATP K20 specification
- Fire retardant: according to RATP K20 specification
- Low smoke: according to RATP K20 specification
- Low toxicity: According to RATP K20 specification
- Low corrosivity: According to RATP K20 specification
- Without Halogen : According to RATP K20 specification

Reaction to fire: B2ca-s1a, d0, a1

DESIGN

- **Conductor:** Bare copper class 1 or 2
- **Insulation:** Cross-linked Polyethylene (XLPE)
- **Assembling:** An inner sheath acting as a filler
- **Outer sheath:** Polyolefin without halogen Colour : black

Core identification

According to NF F 55625

2x: black - blue

3x: black - grey - brown

3G: black - blue - green/yellow

4x: black - blue - brown - black

4G: black - blue - brown - green/yellow

5G: black - blue - brown - black - green/yellow

≥ 7 conductors: black cores printed with numbers with or without green/yellow



Halogen free
IEC/EN 60754-1



Flame retardant
IEC/EN 60332-1-2



Smoke density
IEC 61034-2 & EN 61034-2



Gases corrosivity
IEC/EN 60754-2



Max. conductor temp. in service
90 °C



Operating temp.
-20 ... 60 °C

CHARACTERISTICS

Construction characteristics

| | |
|------------------------|----------------------------------|
| Type of conductor | Stranded, class 2 |
| Conductor material | Plain copper |
| Insulation | XLPE (Cross-linked Polyethylene) |
| Outer sheath | Halogen free polyolefin |
| Halogen free | IEC/EN 60754-1 |
| With Green/Yellow core | No |

Dimensional characteristics

| | |
|-------------------------|--------------------|
| Number of cores | 2 |
| Conductor cross-section | 95 mm ² |
| Minimum outer diameter | - mm |
| Maximum outer diameter | 36.6 mm |
| Approximate weight | 2813 kg/km |

Usage characteristics

| | |
|---------------------------------------|--------------------------|
| Flame retardant | IEC/EN 60332-1-2 |
| Smoke density | IEC 61034-2 & EN 61034-2 |
| Gases corrosivity | IEC/EN 60754-2 |
| Max. conductor temperature in service | 90 °C |
| Operating temperature, range | -20 ... 60 °C |

COMPLEMENT

Bending radius

r = 8 x maximum outer diameter

SELLING AND DELIVERY INFORMATION

Marking

750 V cables: 750 - Nber of cores & cross-section - SH - NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 - Manufacturing number DoP:1000648-FRME + metric marking
1000 V cables: 1000 - Nber of cores & cross-section - SH - NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 - Manufacturing number DoP:1000648-FRME + metric marking