



**Reference:** 10279746  
**EAN 13:** 3427580820632

### FIRE PERFORMANCE CLASS



B2ca-s1a,d0,a1

### CONTACT

Market information  
industryprojects.business@lynxgroup.com

These cables are intended for fixed power or lighting circuits in tunnels, stations and subway stations. These B2ca cables comply with RATP K20 specifications .

### STANDARDS

**Product** EN 50575; EN 60228

**Installation** NF F 55-625

### APPLICATION

These cables are used for fixed power or lighting installations in tunnels and underground stations.

### FIRE PERFORMANCE

- Flame retardant: according to RATP K20 specification
- Fire retardant: according to RATP K20 specification
- Low smoke: according to RATP K20 specification
- Low toxicity: According to RATP K20 specification
- Low corrosivity: According to RATP K20 specification
- Without Halogen : According to RATP K20 specification

**Reaction to fire: B2ca-s1a, d0, a1**

### DESIGN

- **Conductor:** Bare copper class 1 or 2
- **Insulation:** Cross-linked Polyethylene (XLPE)
- **Assembling:** An inner sheath acting as a filler
- **Outer sheath:** Polyolefin without halogen Colour : black

### Core identification

According to NF F 55625

2x: black - blue

3x: black - grey - brown

3G: black - blue - green/yellow

4x: black - blue - brown - black

4G: black - blue - brown - green/yellow

5G: black - blue - brown - black - green/yellow

≥ 7 conductors: black cores printed with numbers with or without green/yellow



Halogen free



Flame retardant



Smoke density  
IEC 61034-2 & EN 61034-2



Gases corrosivity



Max.conductor temp.in service  
90 °C



Operating temp.  
-20 ... 60 °C

## CHARACTERISTICS

### Construction characteristics

Type of conductor	Stranded, class 2
Conductor material	Plain copper
Insulation	XLPE (Cross-linked Polyethylene)
Outer sheath	Halogen free polyolefin
Halogen free	-
With Green/Yellow core	No

### Dimensional characteristics

Number of cores	4
Conductor cross-section	50 mm <sup>2</sup>
Minimum outer diameter	- mm
Maximum outer diameter	45.2 mm
Approximate weight	5802 kg/km

### Usage characteristics

Flame retardant	-
Smoke density	IEC 61034-2 & EN 61034-2
Gases corrosivity	-
Max. conductor temperature in service	90 °C
Operating temperature, range	-20 ... 60 °C

## COMPLEMENT

### Bending radius

r = 8 x maximum outer diameter

## SELLING AND DELIVERY INFORMATION

### Marking

750 V cables: 750 - Nber of cores & cross-section - SH - NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 - Manufacturing number DoP:1000648-FRME + metric marking

1000 V cables: 1000 - Nber of cores & cross-section - SH - NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 - Manufacturing number DoP:1000648-FRME + metric marking