



Reference: 10283020  
EAN 13: 3427580831942

## FIRE PERFORMANCE CLASS



B2<sub>ca</sub> - s1a,d0,a1

## CONTACT

Market information  
industryprojects.business@lynx  
eo.group.com

These cables are intended for fixed power or lighting circuits in tunnels, stations and subway stations. These B2ca cables comply with RATP K20 specifications .

## STANDARDS

Product EN 50575; EN 60228

Installation NF F 55 - 625

## APPLICATION

These cables are used for fixed power or lighting installations in tunnels and underground stations.

## FIRE PERFORMANCE

- Flame retardant: according to RATP K20 specification
- Fire retardant: according to RATP K20 specification
- Low smoke: according to RATP K20 specification
- Low toxicity: According to RATP K20 specification
- Low corrosivity: According to RATP K20 specification
- Without Halogen : According to RATP K20 specification

Reaction to fire: B2ca - s1a, d0, a1

## DESIGN

- Conductor: Bare copper class 1 or 2
- Insulation: Cross - linked Polyethylene (XLPE)
- Assembling: An inner sheath acting as a filler
- Outer sheath: Polyolefin without halogen Colour : black

## Core identification

According to NF F 55625

2x: black - blue

3x: black - grey - brown

3G: black - blue - green/yellow

4x: black - blue - brown - black

4G: black - blue - brown - green/yellow

5G: black - blue - brown - black - green/yellow

7 conductors: black cores printed with numbers with or without green/yellow



Halogen free



IEC 61034 - 2 & EN 61034 - 2



Gases corrosivity



Max. conductor temp.in service  
90 ° C



Operating temp.  
- 20 ... 60 ° C

## CHARACTERISTICS

	2	( )
	XLPE(가	)
Halogen free		-
With Green/Yellow core		-
		9
	2.5 mm <sup>2</sup>	
Minimum outer diameter		- mm
Maximum outer diameter		19.8 mm
( )		516 kg/km
		-
	IEC 61034 - 2 & EN 61034 - 2	
Gases corrosivity		-
Max. conductor temperature in service		90 °C
操作度范		- 20 ... 60 °C

## COMPLEMENT

Bending radius

$r = 8 \times \text{maximum outer diameter}$

## SELLING AND DELIVERY INFORMATION

### Marking

750 V cables: 750 - Nber of cores & cross - section - SH - NF F 55 - 625 - LYNXEO 279 - WW - YY - B2ca - s1a, d0, a1 - Manufacturing number DoP:1000648 - FRME + metric marking

1000 V cables: 1000 - Nber of cores & cross - section - SH - NF F 55 - 625 - LYNXEO 279 - WW - YY - B2ca - s1a, d0, a1 - Manufacturing number DoP:1000648 - FRME + metric marking