



POWER & CONTROL cables without screen

STANDARDS

Product IEC 60228

Installation IEC 60092-350; IEC 60092-353; IEC 60092-360

Test a; IEC 60332-1; IEC 60332-3-22; IEC 60754-1; IEC 61034

APPLICATIONS

Reference: 10283958

CONTACT

Market information
industryprojects.business@lynxogroup.com



Conductor flexibility
Flexible class 5



Halogen free
IEC 60754-1



Rated Voltage U₀/U
(Um)
0.6/ 1 (1.2) kV



Fire retardant
EN IEC 60332-3-22
(cat A)



Flame retardant
IEC 60332-1



Smoke density
IEC 61034



Gases corrosivity
IEC 60754-2



Operating temp.
-30 ... 80 °C

CHARACTERISTICS

Construction characteristics

Conductor material	Bare copper
Conductor flexibility	Flexible class 5
Insulation	XLPE (Cross-linked Polyethylene)
Conductor shape	Circular
Material of filler / inner sheath	Filler if necessary
Outer sheath	Polyolefin
Halogen free	IEC 60754-1
Sheath colour	Black
With Green/Yellow core	Yes

Dimensional characteristics

Number of cores	3
Conductor cross-section	16 mm ²
Nominal outer diameter	16.5 mm
Minimum outer diameter	15.3 mm
Maximum outer diameter	17.7 mm
Approximate weight	553 kg/km

Electrical characteristics

Permissible short circuit current	2.3 kA
Permissible current rating in open air	67 A
Max. DC resistance of the conductor at 20°C	1.15 Ohm/km
Rated Voltage U ₀ /U (U _m)	0.6/ 1 (1.2) kV

Usage characteristics

Fire retardant	EN IEC 60332-3-22 (cat A)
Flame retardant	IEC 60332-1
Smoke density	IEC 61034
Gases corrosivity	IEC 60754-2
Operating temperature, range	-30 ... 80 °C
Max. conductor temperature in service	90 °C

OTHER CHARACTERISTICS

Test Voltage

AC between cores..... 3.5 kV AC

Minimum bending radius for fixed installations MPRX®

- cable diameter ≤ 25 mm..... 4 x outer diameter
- cable diameter > 25 mm..... 6 x outer diameter

Minimum bending radius for fixed installations MPRX® FLEXISHIP®..... 4 x outer diameter