



Reference: 10554182
Country Ref.: 13-MYS24X12P-V1
EAN 13: 8054803101466

CONTACT

Market information
 industryprojects.business@lynxgroup.com

Measuring systems cables acc. to SIEMENS® standard 6FX8008PLUS for extremely dynamic applications, PUR jacket, shielded, oil resistant, flame retardant, halogen free

STANDARDS

Product UL and CSA approval

Normative References

UL Recognized / CSA Approval

AWM 80°C - 30V

AWM 75°C - 30V FT1

Oil resistance:

IEC 50363-10-2

Hydrolysis resistance (jacket):

VDE 0472-02

Flame retardant:

IEC 60332-1-2; FT1; UL1581:EN 50265-2-1

Toxicity:

Halogen free

CHARACTERISTICS

Construction characteristics

Construction type	(12x0.22)C
Conductor material	Tinned copper
Insulation	Polyolefin
Insulation colour	See Tab
Lay Up	Please request detailed data sheet
Taping	Soft tape
Outer sheath	PUR
Sheath colour	Green RAL 6018
Shielding	≥85% tinned copper braid coverage
Halogen free	Yes



Halogen free
Yes



Operating temp.
-30 ... 80 °C



Flame retardant
IEC/EN 60332-1-2; FT1; UL 1581 FT1



Storage temperature, range
-50 ... 80 °C



Oil resistance
EN 50363-10-2

Dimensional characteristics

Nominal outer diameter	6.9 mm
Copper content	48 kg/km
Approximate weight	69 kg/km

Electrical characteristics

Rated Voltage U ₀ /U	30 V
Test voltage	500 V

Mechanical characteristics

Maximum acceleration	50 m/s ²
Bending cycles	5 Mio.
Speed	300 m/min

Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	7.5 (xD)
Operating temperature, range	-30 ... 80 °C
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1
Storage temperature, range	-50 ... 80 °C
Oil resistance	EN 50363-10-2



Halogen free
Yes



Operating temp.
-30 ... 80 °C



Flame retardant
IEC/EN 60332-1-2; FT1; UL 1581 FT1



Storage temperature, range
-50 ... 80 °C



Oil resistance
EN 50363-10-2