



Reference: 13129515
EAN 13: 3427580852954

CONTACT

Market information
industryprojects.business@lynxgroup.com

International Designation: NF F 55-625 (K25) 1000V 1x70 B2ca-s1a,d0,a1

STANDARDS

Product EN 50575; IEC 60228

Installation NF F 55-625

APPLICATION

These cables are used for fixed power or lighting installations (1000 V) and fixed traction circuits (1800 V) in tunnels and underground stations.

FIRE RESISTANCE

- Flame retardant: According to RATP K20 specification
- Fire retardant: According to RATP K20 specification
- Low smoke: According to RATP K20 specification
- Without Halogens: According to RATP K20 specification
- Low Toxicity: According to RATP K20 specification
- Low Corrosivity: According to RATP K20 specification

Reaction to fire: B2ca-s1a, d0, a1

- **Conductor:** Flexible bare copper 5
- **Insulation :** Cross-linked polyethylene (XLPE)
- **Outer sheath:** Polyolefine without halogen, Colour : black

Core Identification

Black



Halogen free
IEC/EN 60754-1



Flame retardant
IEC/EN 60332-1-2



Smoke density
IEC 61034-2 & EN 61034-2



Gases corrosivity
IEC/EN 60754-2



Max.conductor temp.in service
90 °C



Operating temp.
-20 ... 60 °C

CHARACTERISTICS

Construction characteristics

Conductor material	Plain copper
Type of conductor	Flexible, Classe 5
Insulation	XLPE (Cross-linked Polyethylene)
Outer sheath	Halogen free polyolefin
Sheath colour	Black
Halogen free	IEC/EN 60754-1
With Green/Yellow core	No

Dimensional characteristics

Conductor cross-section	70 mm ²
Maximum outer diameter	22.2 mm
Approximate weight	351 kg/km
Minimum outer diameter	- mm

Usage characteristics

Flame retardant	IEC/EN 60332-1-2
Smoke density	IEC 61034-2 & EN 61034-2
Gases corrosivity	IEC/EN 60754-2
Max. conductor temperature in service	90 °C
Operating temperature, range	-20 ... 60 °C

COMPLEMENT

Bending Radius

- $r = 8 \times$ maximum outer diameter

SELLING AND DELIVERY INFORMATION

Marking

1000 V cables: 1000 - Nber of cores & cross-section - S - SH - NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 Manufacturing number DoP:1000291-FRME + metric marking

1800 V cables: 1800 - Nber of cores & cross-section - S - SH - NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 Manufacturing number DoP:1000291-FRME + metric marking