

MULTICORE SENSOR CABLES FOR DRAG CHAIN APPLICATION ADVANCED

HOME RUN CABLES FOR DRAG CHAIN APPLICATION ADVANCED
16x0,34+3x1,0



Home run cables for very dynamic applications MOTIONLINE® ADVANCED

STANDARDS

Product UL and CSA approval

Home run cables for very dynamic applications; PUR Jacket; resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

Reference: 44487211

CONTACT

Market information
industryprojects.business@lynx^{eo}.com
ogroup.com



Halogen free
Yes



Operating temp.
-15 ... 80 °C



Storage temperature, range
-40 ... 80 °C



Flame retardant
IEC 60332-1-2; UL 1581 FT1



Oil resistance
DIN EN 50363-10-2 & DIN EN 60811-404

CHARACTERISTICS

Construction characteristics

Construction type	16x0,34+3x1,0
Conductor material	Bending-resistant conductor with bare copper wires
Insulation	TPM with very low capacitance
Lay Up	cores stranded with filler
Insulation colour	See Tab
Outer sheath	PUR
Sheath colour	Black - RAL 9005
Halogen free	Yes

Dimensional characteristics

Outer Diameter	11.2 mm
Copper content	88 kg/km
Approximate weight	140 kg/km

Electrical characteristics

Rated Voltage U ₀ /U	300 V
Test voltage	2000 V

Mechanical characteristics

Bending cycles	5 Mio.
Speed	180 m/min
Maximum acceleration	20 m/s ²

Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	10 (xD)
Operating temperature, range	-15 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404