



Reference: 79463530

CONTACT

Markets and Products Information
rollingstock.business@lynxeogroup.com

SHEATHED SINGLE CORE POWER CABLES

FLAMEX® EN 50264 - 3 - 1 3600V MM power cables are used for fixed and protected installations. This product range is recommended for narrow spaces where an optimal bending radius is required. FLAMEX® cables are designed to withstand tough working conditions (oil, ozone, temperature variation, etc.). 120 °C conductor temperature is allowed for a 20,000 hours cumulative working time.

STANDARDS

Product EN 50264 - 3 - 1; EN 45545 - HL3; IEC 60228

DESIGN

1. Conductor
Flexible stranded tinned copper class 5 acc. to IEC 60228
Conductor screen
2. Insulation
Cross - linked compound type EI 109 acc. to EN 50264 - 1
Colour: grey
3. Sheath
Cross - linked compound type EM 104 acc. to EN 50264 - 1
Oil, diesel, ozone and UV resistant
Colour: black

Example of marking: FLAMEX EN 50264 - 3 - 1 3600V (mm²) MM
 NSHXAF0E 3.6/6kV | LYNXEO | WW - YYYY

GUIDE TO USE

- Cabling rules are given in EN 50343 and EN 50355
- Permissible current carrying capacities: values and calculation method are given in EN 50343
- Bending radius:
 - Static use: 4 x outer cable diameter (5 x D if D > 10mm)
 - For installation and occasional movements: 10 x outer cable diameter



Conductor flexibility 5



Halogen free
 EN 60754 - 1 & EN 60684 - 2



U_o/U
 (Um)
 3.6 / 6 (7.2) kV



EN 60332 - 1 - 2



Fire retardant
 EN IEC 60332 - 3 - 24 (cat C); EN IEC 60332 - 3 - 25 (EN50305)



EN/IEC 61034 - 2



가
 EN 50305 - 9.2



Operating temp.
 -40 ... 90 °C

CHARACTERISTICS

| | |
|--|--|
| Conductor flexibility | Tin plated copper |
| | 5 |
| Halogen free | Cross - linked compound |
| | Cross - linked compound |
| | EN 60754 - 1 & EN 60684 - 2 |
| Minimum outer diameter | 150 mm ² |
| Maximum outer diameter | 24.7 mm |
| () | 25.5 mm |
| | 1700 kg/km |
| | - mm |
| U _o /U (U _m) | 3.6 / 6 (7.2) kV |
| Fire retardant | EN 60332 - 1 - 2 |
| | EN IEC 60332 - 3 - 24 (cat C); EN IEC 60332 - 3 - 25 (EN50305) |
| 가 | EN/IEC 61034 - 2 |
| 操作度范 | EN 50305 - 9.2 |
| Max. conductor temperature in service | - 40 ... 90 °C |
| Overload maximum core temperature | 90 °C |
| Chemical resistance | - °C |
| Ozone resistance | Excellent |
| U.V resistance | Yes |
| Short - circuit max. conductor temperature | Yes |
| | 200 °C |