



Reference: 79466354

CONTACT

Markets and Products Information
rollingstock.business@lynxéogroup.com

SHIELDED MULTICORES POWER CABLES

FLAMEX® EN 50264-3-2 600V MMS multicores shielded power and control cables are used for protected installations where enhanced electrical screening (EMC) is required. This product range is recommended for installations and connections in narrow spaces where an optimal bending radius is required. FLAMEX® cables are designed to withstand tough working conditions (oil, ozone, temperature variation, etc.). 120° C conductor temperature is allowed for a 20,000 hours cumulative working time.

STANDARDS

Product EN 50264-3-2; EN 45545 - HL3; IEC 60228

DESIGN

1. Conductor

Flexible stranded tinned copper class 5 acc. to IEC 60228
 Optional halogen-free separator tape

2. Insulation

Cross-linked compound type EI 109 acc. to EN 50264-1
 Colour: black (or green/yellow if cable type is G)
 Assembly (option): halogen free foil could be served

3. Screen

Copper wire braid acc. to EN 50264-3-2, halogen-free separator

4. Outer sheath

Cross-linked compound type EM 104 acc. to EN 50264-1
 Oil, diesel, ozone and UV resistant
 Colour: black

Example of marking: FLAMEX EN 50264-3-2 600V n X (or G) ... (mm²) MM S (N)
 HXCSLOE | LYNXEO | WW-YYYY

GUIDE TO USE

- Cabling rules are given in EN 50343 and EN 50355
- Permissible current carrying capacities: values and calculation method are given in EN 50343
- Bending radius:
 - Static use: 4 x outer cable diameter
 - For installation and occasional movements: 8 x outer cable diameter



导线柔软度
 柔软等级5



无卤
 EN 60754-1 & EN
 60684-2



额定电压U₀/U
 0.6/ 1 (1.2) kV



阻燃 - 火焰
 EN 60332-1-2



阻燃
 EN IEC 60332-3-24
 (cat. C); EN IEC
 60332-3-25
 (EN50305)



烟密度
 EN/IEC 61034-2



气体毒性
 EN 50305-9.2



抗电磁干扰
 -

CHARACTERISTICS

结构特性

导体材料	Tin plated copper
导线柔软度	柔软等级5
绝缘	Cross-linked compound
屏蔽	镀锡铜编织
外护套	Cross-linked compound
无卤	EN 60754-1 & EN 60684-2
有绿/黄芯线	无

尺寸特性

芯线数	4
导线截面	2.5 mm ²
外径最小值	10.7 mm
Maximum outer diameter	11.7 mm
近似重量	205 kg/km
导线直径	- mm

电气特性

额定电压U ₀ /U	0.6/ 1 (1.2) kV
-----------------------	-----------------

使用特性

阻燃 - 火焰	EN 60332-1-2
阻燃	EN IEC 60332-3-24 (cat C); EN IEC 60332-3-25 (EN50305)
烟密度	EN/IEC 61034-2
气体毒性	EN 50305-9.2
抗电磁干扰	-
操作温度范围	-40 ... 90 ° C
芯线最高静止温度	90 ° C
Overload maximum core temperature	- ° C
耐化学物质	优异
Ozone resistance	是
抗UV	是
短路最高线芯温度	200 ° C