



**Reference:** ABS 1356 VNB 22

### CONTACT

Market information  
industryprojects.business@lynx  
ogroup.com

**International Designation:** ABS 1356 VNA 22 AWG

**Designed for general purpose aircraft wiring applications.**

Screened and Jacketed Single and Multicores  
UV Laser Printable

### STANDARDS

**Producto** ABS 1356

**Ensayo** prEN 3475

### DESIGN CONSTRUCTION

#### CONDUCTOR

1, 2, 3 or 4 cores ABS 0949 AD

Nickel Copper Clad Aluminium

#### SCREEN

Nickel-plated copper spiral screen

#### JACKET

Polymide tape  
UV PTFE tape

### CORE IDENTIFICATION COLOURS

#### CORE

1 core (VNA) : Grey

2 cores (VNB) : Red - Blue

3 cores (VNC) : Red - Blue - Yellow

4 cores (VND) : Red - Blue - Yellow - Green

**Marking text :** " ADA \*\* FR F++ "

### JACKET IDENTIFICATION

Colour of marking : Grey

**Marking text :** " XXX \*\* FR F++ "

Colour : Green for AWG 22, 18, 14 and 10 - Blue for AWG 24, 20, 16 and 12



Temp. ambiente de utilización  
-65 ... 180 °C



Resistencia a aceites  
Very good resistance to aircraft fluids



Acorde con normativa RoHS  
Si

**CHARACTERISTICS****Características de construcción**

Core identification	Red, Blue
Insulating material	-
Jacket color	Grey
Jacket material	Polyimide tape, UV PTFE tape
Material del conductor	Nickel Copper Clad Aluminum
Number of conductors	2
Pantalla	Nickel plated copper spiral screen

**Características dimensionales**

Diámetro exterior nominal	2,53 mm
Galga (AWG)	22
Screen strands nominal diameter	0,08 mm
Maximum weight	10,16 g/m
Conductor stranding	-
Diámetro exterior máximo	2,7 mm
Nominal weight	9,77 g/m
Número de conductores	2

**Características eléctricas**

Maximal operating frequency	0,0002 MHz
Maximum DC resistance at 20°C	92,9 Ohm/100m
Tensión de operación	600 V

**Características de uso**

Temperatura ambiente de utilización (rango)	-65 ... 180 °C
Resistencia a aceites	Very good resistance to aircraft fluids
Arc tracking resistant	Yes
Acorde con normativa RoHs	Si

**SELLING AND DELIVERY INFORMATION****IDENTIFICATION**

**Core marking in black** ADA \*\* FR F++

**Jacket marking**

XXX \*\* FR F++

Color : Green for AWG 22, 18, 14 and 10 ; Blue for AWG 24, 20, 16 and 12

with :

XXX= Short designation (VNA, VNB, VNC, VND)

\*\* = AWG

FR = Country of origin (FR = France)

F = Manufacturer (F = Lynxéo)

++ = Year of production (i.e. 08 = 2008)