



**Reference:** EN 2267-009D 030P  
(DRD 12)

**Country Ref.:** 10140494

#### CONTACT

Market information  
industryprojects.business@lynx<sup>eo</sup>  
ogroup.com

**International Designation:** DRD 12 030

**Designed for general Purpose Aircraft Wiring Applications.**

Multicores DRA

#### STANDARDS

**Product** EN 2267-009

**Test** prEN 3475

#### DESIGN CONSTRUCTION

##### CORES

2, 3 or 4 cores EN2267-009A

#### IDENTIFICATION

Colours of cores : See table in this datasheet

Colours of marking: White for red and green core, green for blue and yellow cores

Marking : EN DRA \*\* FR F ++

DRA = short designation

\*\* = AWG

FR = Country of origin (FR = France)

F = Manufacturer (F = Lynx<sup>eo</sup>)

++ = Year of production (i.e. 14 = 2014)

### CHARACTERISTICS

#### Construction characteristics

Colour	P
Type of conductor	-
Core identification	Red, Blue, Yellow, Green
Number of conductors	-
Size code	-

#### Dimensional characteristics

Maximum outer diameter	6.48 mm
Nominal outer diameter	6.2 mm
Number of cores	4
Maximum weight	129.08 g/m



Flame retardant  
FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Oil resistance  
Very good resistance to aircraft fluids



RoHS compliant  
Yes



Operating temp.  
-55 ... 260 °C

**Dimensional characteristics**

Nominal weight	119.34 g/m
----------------	------------

**Electrical characteristics**

Maximal operating frequency	0.002 MHz
Maximum DC resistance at 20°C	6.99 Ohm/100m
Operating voltage	600 V

**Usage characteristics**

Flame retardant	FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)
Oil resistance	Very good resistance to aircraft fluids
Arc tracking resistant	Yes
RoHS compliant	Yes
Operating temperature, range	-55 ... 260 °C

**IDENTIFICATION**

Colours of cores	: See table in this datasheet
Colours of marking	: White for red and green core, green for blue and yellow cores
Marking	: EN DRA ** FR F ++ DRA = short designation ** = AWG FR = Country of origin (FR = France) F = Manufacturer (F = Lynx <sup>eo</sup> ) ++ = Year of production (i.e. 14 = 2014)



Flame retardant  
FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Oil resistance  
Very good resistance to aircraft fluids



RoHS compliant  
Yes



Operating temp.  
-55 ... 260 °C