



- Instrumentation cables 170/300 V
- Overall Screen (OS)
- **Oil resistant**

STANDARDS

Test IEC 60332-3-22 Cat.A

APPLICATIONS

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control where chemicals may be present.**

Design

Conductor:

Stranded bare copper class 2

Insulation:

Cross-linked polyethylene (XLPE)

Overall screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

Outer sheath:

Polyvinyl chloride (PVC).

Colour: black.

Other colour on request.

Core identification

Pair: white - black

Quad: white - black - red - blue (2 pair cables assembled as a quad)

White core printed with pair number

Marking

NEXANS 279 XLPE/OA.SCR/PVC 170/300V Nber of pairs & cross-section Cu IEC 60332-3-22(A) MM YYYY Manufacturing number + metric marking

Standards

EN 50288-7 (Design guide-lines)



Rated Voltage U_o/U (Um)
170/300V



Fire retardant
EN IEC 60332-3-22 (cat A)



Oil resistance
Yes



Electro magnetic interference
resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor temp.in
service
90 °C

CONTACT

Market information
industryprojects.business@lynxeogroup.com

CHARACTERISTICS

Construction characteristics

| | |
|--------------------|---|
| Conductor material | Bare copper |
| Type of conductor | Stranded, class 2 |
| Insulation | XLPE (Cross-linked Polyethylene) |
| Overall screen | Tinned copper drain wire + aluminium/polyester tape |
| Outer sheath | PVC |
| Protection | no |

Dimensional characteristics

| | |
|--------------------------|---------------------|
| Number of pairs | 30 |
| Conductor cross-section | 1.5 mm ² |
| Diameter over insulation | 2.16 mm |
| Approximate weight | 1237 kg/km |
| Conductor diameter | 1.5 mm |
| Maximum outer diameter | 30.8 mm |
| Minimum outer diameter | 27.9 mm |

Electrical characteristics

| | |
|---|----------|
| Rated Voltage U ₀ /U (U _m) | 170/300V |
|---|----------|

Usage characteristics

| | |
|--|---------------------------|
| Fire retardant | EN IEC 60332-3-22 (cat A) |
| Oil resistance | Yes |
| Electro magnetic interference resistance | Yes |
| Operating temperature, range | -20 ... 60 °C |
| Max. conductor temperature in service | 90 °C |
| Standard | EN |

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

Tinned copper conductors available on request



Rated Voltage U₀/U (U_m)
170/300V



Fire retardant
EN IEC 60332-3-22 (cat A)



Oil resistance
Yes



Electro magnetic interference
resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor temp.in
service
90 °C