



- Instrumentation cables 170/300 V
- Overall Screen (OS)
- Lead free
- Aliphatic and aromatic hydrocarbons resistant

### STANDARDS

Test IEC 60332-3-22 Cat.A

### APPLICATIONS

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control in moist areas and where aliphatic and aromatic hydrocarbons may be present. Hypron® offers an alternative to conventional lead covered cable and is an environmental friendly solution.**

### Design

#### Conductor:

Stranded bare copper class 2

#### Insulation:

Cross-linked polyethylene (XLPE)

#### Binder tape

#### Bedding

#### Inner sheath:

Polyvinyl chloride (PVC).

Colour: black.

#### Overall screen/sealing barrier:

Tinned copper drain wire,

Aluminium backed polyethylene tape

#### Bedding:

High density polyethylene (PE)

Colour: black

#### Special sheath (intermediate sheath):

Polyamide

#### Outer sheath:

Polyvinyl chloride (PVC).

Colour: black.

Other colour on request.

Fire retardant  
EN IEC 60332-3-22  
(cat A)

Chemical resistance  
**Aliphatic and aromatic hydrocarbons resistant**

Electro magnetic interference resistance  
Yes

Operating temp.  
**-20 ... 60 °C**

Max. conductor temp. in service  
**90 °C**



Lead free  
Yes



Rated Voltage Uo/U  
(Um)  
**170/300V**



Fire retardant  
EN IEC 60332-3-22  
(cat A)



Chemical resistance  
**Aliphatic and aromatic hydrocarbons resistant**



Electro magnetic interference resistance  
Yes



Operating temp.  
**-20 ... 60 °C**



Max. conductor temp. in service  
**90 °C**

### Core identification

Pair: white - black

Quad: white - black - red - blue (2 pair cables assembled as a quad)

All white cores printed with pair numbers

White cores printed with pair numbers and particulars of weights, size and dimensions contained in the technical or commercial documentation of Lynx<sup>eo</sup> is indicative only and shall not be binding on Lynx<sup>eo</sup> or be treated as constituting a representation on the part of Lynx<sup>eo</sup>.

### Marking

NEXANS 279 XLPE/PVC/AL/HDPE/NC/PVC 170/300V Nber of pairs & cross-section

### CONTACT

Market information  
industryprojects.business@lynx<sup>eo</sup>.com  
ogroup.com

### CHARACTERISTICS

#### Construction characteristics

|                     |  |
|---------------------|--|
| Conductor material  | Bare copper  |
| Type of conductor   | Stranded, class 2                                      |
| Insulation          | XLPE (Cross-linked Polyethylene)                       |
| Inner sheath        | PVC  |
| Overall screen      | Tinned copper drain wire + aluminium/polyethylene tape |
| Material of bedding | High-density polyethylene (PE)                         |
| Intermediate sheath | Polyamide  |
| Outer sheath        | PVC  |
| Lead free           | Yes  |
| Protection          | no   |

#### Dimensional characteristics

|                                   |                   |
|-----------------------------------|-------------------|
| Number of pairs                   | 2                 |
| Conductor cross-section           | 1 mm <sup>2</sup> |
| Conductor diameter                | 1.28 mm           |
| Diameter over insulation          | 1.76 mm           |
| Diameter over inner sheath        | 6.8 mm            |
| Diameter over intermediate sheath | 10 mm             |
| Minimum outer diameter            | 15.5 mm           |
| Maximum outer diameter            | 17.1 mm           |
| Approximate weight                | 324 kg/km         |

#### Electrical characteristics

|   |          |
|---|----------|
| Rated Voltage U <sub>0</sub> /U (U <sub>m</sub> ) | 170/300V |
|---|----------|

#### Usage characteristics

|  |   |
|--|---|
| Fire retardant                           | EN IEC 60332-3-22 (cat A)                     |
| Chemical resistance                      | Aliphatic and aromatic hydrocarbons resistant |
| Electro magnetic interference resistance | Yes   |
| Operating temperature, range             | -20 ... 60 °C                                 |
| Max. conductor temperature in service    | 90 °C   |
| Standard                                 | EN  |

### SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) on request.

Minimum bending radius:



Lead free  
Yes



Rated Voltage U<sub>0</sub>/U  
(U<sub>m</sub>)  
170/300V



Fire retardant  
EN IEC 60332-3-22  
(cat A)



Chemical resistance  
Aliphatic and  
aromatic  
hydrocarbons  
resistant



Electro magnetic  
interference resistance  
Yes



Operating temp.  
-20 ... 60 °C



Max. conductor temp. in  
service  
90 °C

15 x outer diameter  
To be doubled during laying operations

Tinned copper conductors available on request



Lead free  
Yes



Rated Voltage  $U_0/U$   
(Um)  
170/300V



Fire retardant  
EN IEC 60332-3-22  
(cat A)



Chemical resistance  
Aliphatic and  
aromatic  
hydrocarbons  
resistant



Electro magnetic  
interference resistance  
Yes



Operating temp.  
-20 ... 60 °C



Max. conductor temp. in  
service  
90 °C