



- Instrumentation cables 170/300 V
- Overall Screen (OS)
- Lead free
- Aliphatic and aromatic hydrocarbons resistant

STANDARDS

Ensayo IEC 60332-3-22 Cat.A

APPLICATIONS

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control in moist areas and where aliphatic and aromatic hydrocarbons may be present. Hypron® offers an alternative to conventional lead covered cable and is an environmental friendly solution.**

Design

Conductor:

Stranded bare copper class 2

Insulation:

Cross-linked polyethylene (XLPE)

Binder tape

Bedding

Inner sheath:

Polyvinyl chloride (PVC).

Colour: black.

Overall screen/sealing barrier:

Tinned copper drain wire,

Aluminium backed polyethylene tape

Bedding:

High density polyethylene (PE)

Colour: black

Special sheath (intermediate sheath):

Polyamide

Outer sheath:

Polyvinyl chloride (PVC).

Colour: black.

Other colour on request.

No propagador del incendio
EN IEC 60332-3-22

Resistencia química
Aliphatic and aromatic hydrocarbons resistant

Resistencia a interferencias electromagnéticas
SI

Temp. ambiente de utilización
-20 ... 60 °C

Max.conductor temp.in service
90 °C



Libre de plomo
SI



Tensión nominal de servicio Uo/U
170/300V



Core identification

Pair: white - black

Quad: white - black - red - blue (2 pair cables assembled as a quad)

White core printed with pair number

All White core printed with pair number and particulars of weights, size and dimensions contained in the technical or commercial documentation of Lynx^{eo} is indicative only and shall not be binding on Lynx^{eo} or be treated as constituting a representation on the part of Lynx^{eo}.

Marking

NEXANS 279 XLPE/PVC/AL/HDPE/NC/PVC 170/300V Nber of pairs & cross-section

CONTACT

Market information
industryprojects.business@lynx^{eo}.com
ogroup.com

CHARACTERISTICS

Características de construcción

Material del conductor	Cobre desnudo
Type of conductor	Stranded, class 2
Aislamiento	XLPE
Cubierta interior	PVC
Overall screen	Tinned copper drain wire + aluminium/polyethylene tape
Material of bedding	High-density polyethylene (PE)
Intermediate sheath	Polyamide
Cubierta exterior	PVC
Libre de plomo	Sí
Protección	no

Características dimensionales

Número de pares	2
Sección del conductor	1,5 mm ²
Diámetro del conductor	1,5 mm
Diámetro sobre aislamiento	2,16 mm
Diameter over inner sheath	7,7 mm
Diameter over intermediate sheath	10,9 mm
Diámetro exterior mínimo	16,4 mm
Diámetro exterior máximo	18,1 mm
Peso aproximado	374 kg/km

Características eléctricas

Tensión nominal de servicio U _o /U	170/300V
-----------------------------------------------	----------

Características de uso

No propagador del incendio	EN IEC 60332-3-22 (cat A)
Resistencia química	Aliphatic and aromatic hydrocarbons resistant
Resistencia a interferencias electromagnéticas	Sí
Temperatura ambiente de utilización (rango)	-20 ... 60 °C
Temperatura máxima del conductor	90 °C
Standard	EN

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) on request.

Minimum bending radius:



Libre de plomo
Sí



Tensión nominal de servicio U_o/U
170/300V



No propagador del incendio
EN IEC 60332-3-22
(cat A)



Resistencia química
Aliphatic and aromatic hydrocarbons resistant



Resistencia a interferencias electromagnéticas
Sí



Temp. ambiente de utilización
-20 ... 60 °C



Max. conductor temp. in service
90 °C

15 x outer diameter
To be doubled during laying operations

Tinned copper conductors available on request



Libre de plomo
SI



Tensión nominal de
servicio U_o/U
170/300V



No propagador del
incendio
EN IEC 60332-3-22
(cat A)



Resistencia química
**Aliphatic and
aromatic
hydrocarbons
resistant**



Resistencia a
interferencias
electromagnéticas
SI



Temp. ambiente de
utilización
-20 ... 60 °C



Max.conductor temp.in
service
90 °C