



### CONTACT

Market information  
industryprojects.business@lynx<sup>eo</sup>  
ogroup.com

- Instrumentation cables 170/300 V
- With lead cover (LC)
- Individual & Overall Screen (IOS)
- **Aliphatic and aromatic hydrocarbons resistant**

### STANDARDS

Test IEC 60331; IEC 60332-3-22 Cat.A

### APPLICATIONS

These instrumentation and communication cables are used to **transmit analogue or digital signals in measurement and process control**. They are well adapted to **underground use** in industrial applications, in moist areas, where **hydrocarbon and mechanical protection are needed**. The **lead cover brings an enhanced resistance to aromatics hydrocarbons**. The **individual screening of each pair limits the consequence of crosstalk**. They maintain circuit integrity when exposed to fire.

### Design

#### Conductor:

Stranded bare copper class 2

#### Insulation:

Silicone rubber (Sil)

#### Individual screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

Polyester tape

#### Overall screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

#### Inner sheath:

Low Smoke Zero Halogen (LSZH)

Colour: black

#### Lead sheath:

#### Bedding (intermediate sheath):

Polyvinyl chloride (PVC)

Colour: black

Fire resistant  
IEC 60331

#### Armour:

Fire retardant  
EN IEC 60332-3-22  
(cat A)

Chemical  
resistance  
**Aliphatic and  
aromatic  
hydrocarbons  
resistant**



Electro magnetic  
interference  
resistance  
**Yes**



Operating temp.  
**-20 ... 60 °C**



Max. conductor  
temp. in service  
**90 °C**

Galvanized steel wires (SWA)

#### Outer sheath:

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Lynx<sup>eo</sup> is indicative only and shall not be binding on Lynx<sup>eo</sup> or be treated as constituting a representation on the part of Lynx<sup>eo</sup>.  
Colour: black

Other colour on request.

### CHARACTERISTICS

#### Construction characteristics

Conductor material	Bare copper
Type of conductor	Stranded, class 2
Insulation	Silicone rubber
Individual screen	Tinned copper drain wire + aluminium/polyester tape
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Inner sheath	Low smoke, zero halogen thermoplastic compound
Lead Sheath	Yes
Intermediate sheath	PVC
Armour type	Galvanized steel wires
Outer sheath	PVC
Protection	Yes

#### Dimensional characteristics

Number of pairs	10
Conductor cross-section	0.75 mm <sup>2</sup>
Conductor diameter	1.1 mm
Diameter over insulation	2.26 mm
Diameter over inner sheath	18.9 mm
Diameter over lead sheath	21.3 mm
Diameter over intermediate sheath	23.3 mm
Diameter over armour	25.8 mm
Minimum outer diameter	26.3 mm
Maximum outer diameter	30.7 mm
Approximate weight	2130 kg/km

#### Electrical characteristics

Rated Voltage U <sub>0</sub> /U (Um)	170/300V
--------------------------------------	----------

#### Mechanical characteristics

Mechanical resistance to impacts	Good
----------------------------------	------

#### Usage characteristics

Fire resistant	IEC 60331
Fire retardant	EN IEC 60332-3-22 (cat A)
Chemical resistance	Aliphatic and aromatic hydrocarbons resistant
Electro magnetic interference resistance	Yes
Operating temperature, range	-20 ... 60 °C
Max. conductor temperature in service	90 °C
Standard	EN



Rated Voltage U<sub>0</sub>/U (Um)  
170/300V



Mechanical resistance to impacts  
Good



Fire resistant  
IEC 60331



Fire retardant  
EN IEC 60332-3-22 (cat A)



Chemical resistance  
Aliphatic and aromatic hydrocarbons resistant



Electro magnetic interference resistance  
Yes



Operating temp.  
-20 ... 60 °C



Max. conductor temp. in service  
90 °C

**SELLING AND DELIVERY INFORMATION**

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) on request.

Minimum bending radius:

10 x outer diameter  
To be doubled during laying operations

Tinned copper conductors available on request



Rated Voltage U<sub>0</sub>/U  
(Um)  
**170/300V**



Mechanical  
resistance to  
impacts  
**Good**



Fire resistant  
**IEC 60331**



Fire retardant  
**EN IEC 60332-3-22  
(cat A)**



Chemical  
resistance  
**Aliphatic and  
aromatic  
hydrocarbons  
resistant**



Electro magnetic  
interference  
resistance  
**Yes**



Operating temp.  
**-20 ... 60 °C**



Max. conductor  
temp. in service  
**90 °C**